



Dahua Technology CS4220-16GT-190 Gestionado L2 Gigabit Ethernet (10/100/1000) Energía sobre Ethernet (PoE) 1U Negro



Marca : Dahua Technology

Código del producto: DH-CS4220-16GT-190

Nombre del producto : CS4220-16GT-190

Dahua Technology CS4220-16GT-190. Tipo de interruptor: Gestionado, Capa del interruptor: L2. Puertos tipo básico de conmutación RJ-45 Ethernet: Gigabit Ethernet (10/100/1000), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 18. Tabla de direcciones MAC: 8000 entradas, Capacidad de conmutación: 40 Gbit/s. Estándares de red: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x, IEEE.... Energía sobre Ethernet (PoE). Montaje en rack, Factor de forma: 1U

Management features		Design	
Switch type *	Managed	LED indicators	Link, PoE, Power, System
Switch layer	L2	Performance	
Web-based management	✓	Mean time between failures (MTBF)	762116 h
Cloud-managed	✓	Power	
Ports & interfaces		Power source *	AC/DC/PoE
Basic switching RJ-45 Ethernet ports quantity *	18	Power supply included *	✓
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	AC input voltage	100 - 240 V
Gigabit Ethernet (copper) ports quantity	18	AC input frequency	47/63 Hz
SFP module slots quantity	2	Power consumption (max)	212 W
Network		Power over Ethernet (PoE)	
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power over Ethernet (PoE) *	✓
10G support *	✗	Power over Ethernet (PoE) ports quantity	16
Flow control support	✓	Power over Ethernet (PoE) power per port	30 W
VLAN support	✓	Total Power over Ethernet (PoE) budget	190 W
Virtual LAN features	Port-based VLAN	Operational conditions	
Number of VLANs	32	Operating temperature (T-T)	-10 - 55 °C
Data transmission		Storage temperature (T-T)	-40 - 70 °C
Switching capacity *	40 Gbit/s	Operating relative humidity (H-H)	5 - 95%
Forwarding rate	29.76 Mpps	Storage relative humidity (H-H)	5 - 95%
MAC address table *	8000 entries	Weight & dimensions	
Jumbo frames support	✓	Width	440 mm
Jumbo frames	15000	Depth	220 mm
Packet buffer memory	0.5 MB	Height	44 mm
Security		Weight	2.32 kg
DHCP features	DHCP client	Packaging data	
Loop protection	✓	Package width	540 mm
Design		Package depth	342 mm
Rack mounting *	✓	Package height	90 mm
Form factor	1U	Package weight	2.97 kg
Product colour	Black		
Housing material	Metal		
Reset button	✓		

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date