

## Dahua Technology PoE SF1026LP No administrado L2 Fast Ethernet (10/100) Energía sobre Ethernet (PoE) Negro

Marca: Dahua Technology

Familia de productos: PoE

Código del producto: DH-SF1026LP



## Nombre del producto:

SF1026LP

Dahua Technology PoE SF1026LP. Tipo de interruptor: No administrado, Capa del interruptor: L2. Puertos tipo básico de conmutación RJ-45 Ethernet: Fast Ethernet (10/100), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 26. Tabla de direcciones MAC: 8000 entradas, Capacidad de conmutación: 8.8 Gbit/s. Estándares de red: IEEE 802.3, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at, IEEE 802.3u, IEEE 802.3x. Energía sobre Ethernet (PoE). Montaje de pared, Montaje en rack

Management features		Design	
Switch type *	Unmanaged	Wall mountable	✓
Switch layer	L2	Performance	
Quality of Service (QoS) support	×	Mean time between failures (MTBF)	448074 h
Ports & interfaces		Power	
Basic switching RJ-45 Ethernet ports quantity *		Power source * AC input voltage	AC 100 - 240 V
Basic switching RJ-45 Ethernet ports type *	Fast Ethernet (10/100)	AC input frequency	50/60 Hz
Fast Ethernet (copper) ports quantity	24	Input current Power consumption (max)	3.96 A 190 W
Gigabit Ethernet (copper) ports quantity	2	Power over Ethernet (PoE)	
Uplink ports quantity	2	Power over Ethernet (PoE) *	✓
Network	IFFE 002 2 IFFE 002 2-b IFFE	Total Power over Ethernet (PoE) budget	190 W
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3u,	Operational conditions	
10G support *	EEE 802.3x	Operating temperature (T-T) Storage temperature (T-T)	-10 - 55 °C -40 - 85 °C
Flow control support	<b>✓</b>	Operating relative humidity (H-H)	10 - 90%
Link aggregation	X	Storage relative humidity (H-H)	5 - 95%
Spanning tree protocol  VLAN support	×	Weight & dimensions	
	^	Width Depth	189.5 mm 285 mm
Data transmission	0.0.00	Height	43.7 mm
Switching capacity * Forwarding rate	8.8 Gbit/s 6.5472 Mpps	Weight	1.71 kg
MAC address table *	8000 entries	Packaging data	
Jumbo frames support	✓	Package width	299 mm
Jumbo frames	9000	Package depth	369 mm
Packet buffer memory	4 MB	Package height	81 mm
Security		Package weight	2.37 kg
Access Control List (ACL)	×	Sustainability	
Design		Sustainability compliance	✓
Rack mounting *	✓	Certificates	
Product colour Housing material	Black Steel	Compliance certificates	CE



6923172572028

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.