

Dahua Technology DH-MPTZ3300-2030URA-NT cámara de vigilancia Torreta Cámara de seguridad IP Exterior 1920 x 1080 Pixeles

Marca: Dahua Technology

Código del producto: DHMPTZ3300-2030URA-NT

Nombre del producto: DH-MPTZ3300-2030URA-NT

Dahua Technology DH-MPTZ3300-2030URA-NT. Tipo: Cámara de seguridad IP, Colocación compatible: Exterior, Tecnología de conectividad: Alámbrico. Color del producto: Gris, Factor de forma: Torreta, Código IP (International Protection): IP66. Ángulo de visión del objetivo, horizontal: 67.8 - 2.77°, Ángulo de inclinación: -90 - 90°, Velocidad de inclinación: 60 °/seg. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.8 mm (1 / 2.8"). Zoom óptico: 30x, Intervalo de longitud focal: 4.5 - 135 mm, Enfoque: Motorizado/Manual

| Performance | | Video | |
|--|---|--|--|
| Type * Placement supported * Connectivity technology * | IP security camera Outdoor Wired | Maximum resolution * Total megapixels * Video compression formats | 1920 x 1080 pixels 2.42 MP H.264, M-JPEG |
| PTZ control PTZ modes | 5 Pattern, 8 Tour, Auto scan, Preset point | Supported graphics resolutions | 352 x 240, 352 x 288, 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080) |
| Porm factor * Product colour * International Protection (IP) code Camera | Turret Grey IP66 | Supported video modes Frame rate Gain control type Back Light Compensation (BLC) Highlight Compensation (HLC) Digital Wide Dynamic Range | 720p, 1080p 30 fps Auto/Manual |
| Camera pan control | ✓ | (DWDR) | ✓ |
| Camera tilt control | ✓ | Audio | |
| Lens viewing angle, horizontal | 67.8 - 2.77° | Signal-to-Noise Ratio (SNR) | 55 dB |
| Tilt angle range | -90 - 90° | Network | |
| Tilt speed Pan range Pan speed Camera shutter type Camera shutter speed | 60 °/sec 0 - 360° 80 °/sec Electronic 1 - 1/30000 s | Ethernet LAN * Ethernet interface type Supported network protocols | Fast Ethernet IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, |
| Image sensor | | | PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour |
| Optical sensor size Sensor type * | 25.4 / 2.8 mm (1 / 2.8") CMOS | Wi-Fi * Bluetooth * | × |
| Lens system | | Number of users | 32 user(s) |
| Zoom capability | ✓ | Storage | |
| Optical zoom | 30x | Built-in HDD * | X |
| Focal length range Auto focus | 4.5 - 135 mm ✓ | Power | |
| Focus Maximum aperture number Minimum aperture number | Motorized/Manual 4.4 1.6 | Power source type * Power consumption (typical) DC output voltage | DC 60 W 12 |
| Night vision | | Operational conditions | |
| Night vision * Night vision distance | √ 150 m | Operating temperature (T-T) Operating relative humidity (H-H) | -30 - 65 °C 0 - 95% |
| LED type | IR | Weight & dimensions | |
| | | Width Depth Height Weight | 375 mm 210 mm 248 mm 7.5 kg |

