


TP-Link Omada ER7412-M2 enrutador 2.5 Gigabit Ethernet, Gigabit Ethernet Negro

Marca : TP-Link Familia de productos: Omada Código del producto: ER7412-

M2

Nombre del producto:

ER7412-M2



Flash: 128 MB, Memoria interna: 1024 MB, Tipo de memoria interna: DDR4





WAN connection		Security	
Ethernet WAN *	✓	Network address translation (NAT)	✓
DSL WAN *	×	VPN tunnels quantity	80
SIM card slot *	×	Certificates	
3G/4G USB modem compatibility * SFP WAN *	V V V V V V V V V V	Compliance certificates	CE, Federal Communications Commission (FCC)
Network		Packaging content	
Networking standards *	IEEE 802.1Q, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Cables included	AC, LAN (RJ-45)
		Quick start guide	✓
	2.5 Gigabit Ethernet, Gigabit	Features	
Ethernet interface type *	Ethernet	Flash memory	128 MB
Ethernet LAN data rates	10,100,1000,2500 Mbit/s	Internal memory	1024 MB
Static route	✓	Internal memory type	DDR4
VLAN support Management features Web-based management *	*	Windows operating systems supported	Windows 10, Windows 11, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows 98SE, Windows NT, Windows Vista, Windows XP
Universal Plug and Play (UPnP)	·	Mac operating systems supported	Willdows ∧P
Reset button	·	Linux operating systems supported	
Ports & interfaces		Design	
Ethernet LAN (RJ-45) ports * WAN/Ethernet LAN ports quantity	7 2	Product colour * Rack mounting	Black ✓
SFP module slots quantity Number of console ports	2 1	Power	
USB ports quantity	1	Power consumption (max)	18.5 W
Protocols		AC input voltage AC input frequency	100 - 240 V 50/60 Hz
DMZ support	✓	no input irequeity	30/00 112

Protocols		Operational conditions	
DHCP server *	✓	Operating temperature (T-T)	0 - 45 °C
Security		Storage temperature (T-T) Operating relative humidity (H-H)	-40 - 70 °C 10 - 90%
Security algorithms *	128-bit AES, 192-bit AES, 256-bit AES, DES, MD5, SHA-1, SHA-2, SHA-384, SHA-512	Storage relative humidity (H-H)	5 - 90%
		Weight & dimensions	
URL filtering	✓	Width	294 mm
DoS attack prevention	✓	Depth	180 mm
ARP attack prevention	✓	Height	44 mm
ICMP attack prevention	✓		
Access Control List (ACL)	✓		









Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.