



TP-Link Omada EAP683 UR punto de acceso inalámbrico 6000 Mbit/s Blanco Energía sobre Ethernet (PoE)

Marca : TP-Link Familia de productos: Omada Código del producto: EAP683 UR

Nombre del producto : EAP683 UR

TP-Link Omada EAP683 UR. 2.4 GHz, 5 GHz, Rango máximo de transferencia de datos: 6000 Mbit/s. Algoritmos de seguridad: HTTPS, SNMP, SNMPv2, SNMPv3, SSH. Ethernet LAN, velocidad de transferencia de datos: 10,100,1000,2500 Mbit/s. Energía sobre Ethernet (PoE). Color del producto: Blanco



Features		Management features	
2.4 GHz *	✓	Firmware upgradeable	✓
5 GHz *	✓	Ports & interfaces	
6 GHz *	✗	Ethernet LAN (RJ-45) ports *	1
Maximum data transfer rate *	6000 Mbit/s	DC-in jack	✓
Maximum data transfer rate (2.4 GHz)	1148 Mbit/s	Power	
Maximum data transfer rate (5 GHz)	4804 Mbit/s	Power over Ethernet (PoE) *	✓
Ethernet LAN data rates	10,100,1000,2500 Mbit/s	DC voltage range	12 V
Frequency band	2.4 - 6 GHz	Design	
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, IEEE 802.3at	Placement *	Ceiling, Wall
		Product colour *	White
Number of users	510 user(s)	Reset button	✓
Automatic channel selection	✓	LED indicators	✓
Automatic channel scanning	✓	Antenna	
MIMO	✓	Antenna type *	Internal
MIMO type	Multi User MIMO	Antenna direction type	Omni-directional
Fast roaming	✓	Antenna gain level (max)	5 dBi
VLAN support	✓	Weight & dimensions	
Rate limiting	✓	Width	220 mm
Band steering	✓	Depth	220 mm
Airtime Fairness (ATF)	✓	Height	32.5 mm
Quality of Service (QoS) support	✓	Packaging data	
BeamForming	✓	Package type	Box
Security		Packaging content	
Security algorithms *	HTTPS, SNMP, SNMPv2, SNMPv3, SSH	Quantity per pack	1 pc(s)
		Mounting kit	✓

Security		Packaging content	
MAC address filtering	✓	Quick start guide	✓
Service Set Identifier (SSID) features	Multiple SSIDs	Operational conditions	
Access Control List (ACL)	✓	Operating relative humidity (H-H)	10 - 90%
Management features		Operating temperature (T-T)	0 - 40 °C
Syslog	✓	Storage temperature (T-T)	-40 - 70 °C
		Storage relative humidity (H-H)	5 - 90%




8885020621938



0810142821018



810142821018



8885020621945

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date