



HiLook IPC-T241H-C(2.8mm) Torreta Cámara de seguridad IP
Interior y exterior 2560 x 1440 Píxeles Techo/pared

Marca : HiLook

Código del producto: IPC-T241H-C(2.8MM)(HILOOKSTD)

Nombre del producto : IPC-T241H-C(2.8mm)

HiLook IPC-T241H-C(2.8mm). Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared, Color del producto: Blanco, Factor de forma: Torreta. Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 104°, Ángulo de visión del objetivo, vertical: 57°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.8 mm (1 / 2.8"). Distancia de detección: 53 m, Distancia de observación: 21 m, Distancia de reconocimiento: 10 m



Performance		Video	
Type *	IP security camera	Highlight Compensation (HLC)	✓
Placement supported *	Indoor & outdoor	Region of Interest (ROI) encoding	✓
Connectivity technology *	Wired	Audio	
Wide Dynamic Range (WDR)	✓	Signal-to-Noise Ratio (SNR)	52 dB
Day/night mode	✓	Network	
Infrared (IR) cut-off filter	✓	Ethernet LAN *	✓
Number of languages	2	Ethernet interface type	Fast Ethernet
Languages support	English, Ukrainian	Supported network protocols	TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTCP, RTSP, NTP, IGMP, IPv4, IPv6, UDP, QoS, SNMP, DDNS
Design		Wi-Fi *	✗
Form factor *	Turret	Bluetooth *	✗
Mounting type *	Ceiling/wall	Number of users	32 user(s)
Product colour *	White	User access level	Administrator, Operator, User
Housing material	Plastic	Client interoperability	iVMS-4200
Protection features	Water resistant	Live view	✓
International Protection (IP) code	IP67	Number of simultaneous live view channels	6 channels
Camera		Storage	
Minimum illumination	0 lx	Built-in HDD *	✗
Angle of rotation	360°	Ports & interfaces	
Lens viewing angle, horizontal	104°	Ethernet LAN (RJ-45) ports	1
Lens viewing angle, vertical	57°	Security	
Lens viewing angle, diagonal	123°	Password protection	✓
Tilt angle range	0 - 75°	Video motion detection	✓
Pan range	0 - 360°	Privacy protection	✓
Camera shutter speed	1/3 - 1/100000 s		
Number of Privacy masking areas	1		
Image sensor			
Number of sensors	1		
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")		

Image sensor		Security	
Progressive scan	✓	Heartbeat	✓
Sensor type *	CMOS	Mirror	✓
Lens system		Digital watermark	✓
Number of lenses *	1	Password reset via email	✓
Detect distance	53 m	Audit log	✓
Observe distance	21 m	Digest authentication	✓
Recognize distance	10 m	Management features	
Maximum aperture number	2.2	Web-based management	✓
Identify distance	5 m	Power	
Fixed focal length	2.8 mm	Power source type *	DC, PoE
Night vision		Power consumption (max)	5 W
Night vision *	✓	Power consumption (Power over Ethernet (PoE))	6.5 W
Night vision distance	20 m	DC output voltage	12
LED type	IR	DC output current	0.42 A
Infra-red wavelength	850 nm	Operational conditions	
Video		Operating temperature (T-T)	-30 - 45 °C
Maximum resolution *	2560 x 1440 pixels	Storage temperature (T-T)	-30 - 45 °C
Total megapixels *	4 MP	Operating relative humidity (H-H)	0 - 95%
Video compression formats	H.264, H.264+, H.265, H.265+, M-JPEG	Storage relative humidity (H-H)	0 - 95%
Supported graphics resolutions	640 x 360, 640 x 480 (VGA), 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2560 x 1440	Weight & dimensions	
Frame rate	25 fps	Height	88.4 mm
Video streaming	✓	Diameter	11.2 cm
Noise reduction	✓	Weight	325 g
Noise reduction technology	3D noise reduction	Packaging data	
Image quality adjustment	Brightness, Contrast, Saturation, Sharpness	Package width	134 mm
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)	Package depth	134 mm
Bit rate	32 Kbps - 8 Mbps	Package height	108 mm
Back Light Compensation (BLC)	✓	Package weight	563 g
		Sustainability	
		Compliance certificates	CB, CE, Electromagnetic Compatibility (EMC), KC, Low Voltage Directive (LVD), REACH, RoHS, WEEE
		Packaging content	
		Number of cameras *	1
		Technical details	
		Lens mount interface	M12

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date