

## EZVIZ CS-C6W cámara de vigilancia Esférico Cámara de seguridad IP Interior 2560 x 1440 Pixeles Escritorio

Widows St.

Marca: EZVIZ Código del producto: CS-C6W

Nombre del producto: CS-C6W

EZVIZ CS-C6W. Tipo: Cámara de seguridad IP, Colocación compatible: Interior, Tecnología de conectividad: Inalámbrico y alámbrico. Tipo de montaje: Escritorio, Color del producto: Negro, Gris, Factor de forma: Esférico. Ángulo de visión del objetivo, horizontal: 83°, Ángulo de visión del objetivo, vertical: 57°, Ángulo de visión de la lente, diagonal: 104°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.7 mm (1 / 2.7"). Zoom digital: 4x, Distancia focal fija: 4 mm

Performance		Video	
	ID coough, comore		
Type * Placement supported * Connectivity technology *	IP security camera Indoor Wired & Wireless	Back Light Compensation (BLC)	✓
		Network	
Wide Dynamic Range (WDR)	<b>✓</b>	Ethernet LAN *	✓
Day/night mode	<b>✓</b>	Ethernet interface type	Fast Ethernet
Infrared (IR) cut-off filter	✓	Wi-Fi *	•
Certification	CE/WEEE/REACH/RoHS/FCC/UL	Wi-Fi standards Wi-Fi data rate (max)	802.11b, 802.11g, Wi-Fi 4 (802.11n) 72 Mbit/s
Design		Bluetooth *	X
Form factor *	Spherical		
Mounting type *	Desk	Storage	
Product colour *	Black, Grey	Built-in HDD *	X
Camera		Card reader integrated	✓ MicroCD /TroncFlook)
Camera pan control	✓	Compatible memory cards  Maximum memory card size	MicroSD (TransFlash) 256 GB
Camera tilt control	<b>✓</b>	Ports & interfaces	
Minimum illumination  Lens viewing angle, horizontal	0 lx 83°	Ethernet LAN (RJ-45) ports	1
Lens viewing angle, vertical	57°	Security	
Lens viewing angle, diagonal	104°	Security algorithms	64-bit WEP, 128-bit WEP, WPA,
Tilt angle range	0 - 75°		WPA-PSK, WPA2, WPA2-PSK
Pan range	0 - 340°	Management features	
Image sensor	05.4.40.7 (4.40.7%)	Cloud-managed *	<b>/</b>
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	Cloud services supported	EZVIZ Cloud
Progressive scan Sensor type *	CMOS	Power	
	CHOS	Power source type *	DC
Lens system		Power consumption (max) DC output voltage	8 W 5
Zoom capability	<b>√</b>	DC output current	2 A
Digital zoom  Minimum aperture number	4x 2	Operational conditions	
Fixed focal length	4 mm	Operating temperature (T-T)	-10 - 45 °C
Night vision		Operating relative humidity (H-H)	0 - 95%
Night vision *	<b>✓</b>	Weight & dimensions	
Night vision distance	10 m	Height	90.6 mm
LED type	IR	Diameter	9.58 cm
Video		Weight	252 g
Maximum resolution *	2560 x 1440 pixels	Packaging data	
Video compression formats	H.264, H.265	Package width	126 mm
Frame rate	25 fps	Package depth	126 mm
		Package height Package weight	160 mm 513 g
		rackage weight	515 y

	CONTANT
Packaging	COLLEGIE

Number of cameras \*

1

