



Lenovo ThinkSystem SR250 V3 servidor Bastidor (1U) Intel Xeon E E-2434 3.4 GHz 16 GB DDR5-SDRAM 300 W



Marca : Lenovo

Familia de productos:
ThinkSystem

Código del producto:
7DCLA02CLA

Nombre del producto : SR250
V3

Lenovo ThinkSystem SR250 V3. Familia de procesador: Intel Xeon E, Frecuencia del procesador: 3.4 GHz, Modelo del procesador: E-2434. Memoria interna: 16 GB, Tipo de memoria interna: DDR5-SDRAM, Diseño de memoria (ranuras x tamaño): 1 x 16 GB. Ethernet, Tecnología de cableado: 10/100/1000Base-T(X). Fuente de alimentación: 300 W. Tipo de chasis: Bastidor (1U)

Processor		Ports & interfaces	
Processor manufacturer *	Intel	USB 2.0 ports quantity	2
Processor family *	Intel Xeon E	USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	3
Processor model *	E-2434	VGA (D-Sub) ports quantity	1
Processor frequency *	3.4 GHz	Serial ports quantity	1
Processor boost frequency	5 GHz		
Performance cores	4		
Processor cores	4		
Processor cache	12 MB		
Motherboard chipset	Intel C266		
Number of processors installed	1		
Memory		Design	
Internal memory *	16 GB	Chassis type *	Rack (1U)
Internal memory type *	DDR5-SDRAM	Product colour	Black, Silver
Memory slots	4x DIMM		
ECC	✓		
Memory clock speed	4800 MHz		
Memory layout (slots x size)	1 x 16 GB		
Maximum internal memory *	128 GB		
Storage		Performance	
RAID levels	0, 1, 5, 10	Remote administration	XClarity Administrator
Internal drive bays	4	Trusted Platform Module (TPM)	✓
Supported storage drive interfaces	SAS, Serial ATA	Trusted Platform Module (TPM) version	2.0
Graphics		Software	
On-board graphics card	✓	Compatible operating systems *	Microsoft Windows Server Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESXi
Maximum graphics card memory	16 MB		
Network		Power	
LAN controller	Broadcom BCM5720	Power supply *	300 W
Ethernet LAN	✓	Power supply input voltage	100 - 240 V
Cabling technology	10/100/1000Base-T(X)	Power supply input frequency	50/60 Hz
Ethernet interface type	Gigabit Ethernet		
Ports & interfaces		Operational conditions	
Ethernet LAN (RJ-45) ports *	2	Storage temperature (T-T)	-40 - 60 °C
		Storage relative humidity (H-H)	8 - 90%
		Operating altitude	0 - 3050 m
		Weight & dimensions	
		Width	434.4 mm
		Depth	561 mm
		Height	43 mm
		Technical details	
		Supported storage drives form factor (rear)	3.5"

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 03-FEB-2025. Prints or copies of Information are only valid on the printed Publication date