



## Dahua Technology DH-AS5600-24GF4XF dispositivo de redes Gestionado L3 Gigabit Ethernet (10/100/1000) 1U Negro

**Marca :** Dahua Technology

**Código del producto:** DH-AS5600-24GF4XF

**Nombre del producto :** DH-AS5600-24GF4XF

Dahua Technology DH-AS5600-24GF4XF. Tipo de interruptor: Gestionado, Capa del interruptor: L3. Puertos tipo básico de conmutación RJ-45 Ethernet: Gigabit Ethernet (10/100/1000), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 8, Puerto de consola: RJ-45. Tabla de direcciones MAC: 16000 entradas, Capacidad de conmutación: 598 Gbit/s. Estándares de red: IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z. Montaje en rack, Factor de forma: 1U

Management features		Security	
Switch type *	Managed	Access Control List (ACL)	✓
Switch layer	L3	IGMP snooping	✓
Quality of Service (QoS) support	✓	Multicast features	
ARP inspection	✓	Multicast support	✓
Configuring Location Settings (CLI)	✓	Design	
Ports & interfaces		Rack mounting *	✓
Basic switching RJ-45 Ethernet ports quantity *	8	Form factor	1U
Basic switching RJ-45 Ethernet ports type *	Gigabit Ethernet (10/100/1000)	Product colour	Black
SFP module slots quantity	24	Housing material	Metal
SFP+ module slots quantity	4	Power	
Console port	RJ-45	Power source *	AC
Network		Power supply included *	✓
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	AC input voltage	100 - 240 V
		AC input frequency	50/60 Hz
10G support *	✓	Input current	2.5 A
Port mirroring	✓	Power over Ethernet (PoE)	
IP routing	✓	Power over Ethernet (PoE) *	✗
Policy-based routing	✓	Operational conditions	
Flow control support	✓	Operating temperature (T-T)	-5 - 45 °C
Link aggregation	✓	Storage temperature (T-T)	-40 - 70 °C
IPv4 routes	12000	Operating relative humidity (H-H)	5 - 95%
VLAN support	✓	Storage relative humidity (H-H)	5 - 95%
Number of VLANs	4000	Weight & dimensions	
Data transmission		Width	440 mm
Switching capacity *	598 Gbit/s	Depth	360 mm
Forwarding rate	128 Mpps	Height	43.6 mm
MAC address table *	16000 entries	Weight	6 kg
Static route	✓	Packaging data	
Jumbo frames support	✓	Package width	590 mm
Packet buffer memory	1.5 MB	Package depth	480 mm
Security		Package height	135 mm
DHCP features	DHCP client, DHCP relay, DHCP server, DHCP snooping	Certificates	
		Certification	CE; FCC

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date