

HiLook IPC-B141H-C(2.8mm) Bala (forma) Cámara de seguridad IP Interior y exterior 2560 x 1440 Pixeles Techo/pared

Marca : HiLook

Código del producto: IPC-B141H-C(2.8MM)(HILOOKSTD)

Nombre del producto : IPC-B141H-C(2.8mm)

HiLook IPC-B141H-C(2.8mm). Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared, Color del producto: Blanco, Factor de forma: Bala (forma). Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 104°, Ángulo de visión del objetivo, vertical: 57°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.8 mm (1 / 2.8"). Distancia de detección: 53 m, Distancia de observación: 21 m, Distancia de reconocimiento: 10 m



| Performance                        |                          | Video                                     |   |
|------------------------------------|--------------------------|---|---|
| Type *                             | IP security camera       | Region of Interest (ROI) encoding         | ✓   |
| Placement supported *              | Indoor & outdoor         | Audio                                     |   |
| Connectivity technology *          | Wired                    | Signal-to-Noise Ratio (SNR)               | 52 dB   |
| Wide Dynamic Range (WDR)           | ✓                        | Network                                   |   |
| Day/night mode                     | ✓                        | Ethernet LAN *                            | ✓   |
| Number of languages                | 2                        | Ethernet interface type                   | Fast Ethernet   |
| Languages support                  | English, Ukrainian       | Supported network protocols               | TCP/IP, ICMP, DHCP, DNS, HTTP, RTP, RTCP, RTSP, NTP, IGMP, IPv4, IPv6, UDP, QoS, SNMP, DDNS |
| Design                             |                          | Wi-Fi *                                   | ✗   |
| Form factor *                      | Bullet                   | Bluetooth *                               | ✗   |
| Mounting type *                    | Ceiling/wall             | Number of users                           | 32 user(s)  |
| Product colour *                   | White                    | User access level                         | Administrator, Operator, User   |
| Housing material                   | Plastic                  | Client interoperability                   | iVMS-4200   |
| Protection features                | Water resistant          | Live view                                 | ✓   |
| International Protection (IP) code | IP67                     | Number of simultaneous live view channels | 6 channels  |
| Camera                             |                          | Storage                                   |   |
| Minimum illumination               | 0 lx                     | Built-in HDD *                            | ✗   |
| Angle of rotation                  | 360°                     | Ports & interfaces                        |   |
| Lens viewing angle, horizontal     | 104°                     | Ethernet LAN (RJ-45) ports                | 1   |
| Lens viewing angle, vertical       | 57°                      | Security                                  |   |
| Lens viewing angle, diagonal       | 123°                     | Password protection                       | ✓   |
| Tilt angle range                   | 0 - 90°                  | Video motion detection                    | ✓   |
| Pan range                          | 0 - 360°                 | Privacy protection                        | ✓   |
| Camera shutter speed               | 1/3 - 1/100000 s         | Heartbeat                                 | ✓   |
| Number of Privacy masking areas    | 1                        | Mirror                                    | ✓   |
| Image sensor                       |                          | Digital watermark                         | ✓   |
| Number of sensors                  | 1                        | Password reset via email                  | ✓   |
| Optical sensor size                | 25.4 / 2.8 mm (1 / 2.8") | Audit log                                 | ✓   |
| Progressive scan                   | ✓                        |   |   |
| Sensor type *                      | CMOS                     |   |   |
| Lens system                        |                          |   |   |
| Number of lenses *                 | 1                        |   |   |
| Detect distance                    | 53 m                     |   |   |

| Lens system                    |   | Security                                      |   |
|--------------------------------|---|---|---|
| Observe distance               | 21 m  | Digest authentication                         | ✓   |
| Recognize distance             | 10 m  | Management features                           |   |
| Maximum aperture number        | 2.2   | Web-based management                          | ✓   |
| Identify distance              | 5 m   | Power   |   |
| Fixed focal length             | 2.8 mm  | Power source type *                           | DC, PoE   |
| Night vision                   |   | Power consumption (max)                       | 5 W   |
| Night vision *                 | ✓   | Power consumption (Power over Ethernet (PoE)) | 6.5 W   |
| Night vision distance          | 20 m  | DC output voltage                             | 12  |
| LED type                       | IR  | DC output current                             | 0.42 A  |
| Infra-red wavelength           | 850 nm  | Operational conditions                        |   |
| Video                          |   | Operating temperature (T-T)                   | -30 - 45 °C   |
| Maximum resolution *           | 2560 x 1440 pixels  | Storage temperature (T-T)                     | -30 - 45 °C   |
| Total megapixels *             | 4 MP  | Operating relative humidity (H-H)             | 0 - 95%   |
| Video compression formats      | H.264, H.264+, H.265, H.265+, M-JPEG  | Storage relative humidity (H-H)               | 0 - 95%   |
| Supported graphics resolutions | 640 x 360, 640 x 480 (VGA), 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2560 x 1440 | Weight & dimensions                           |   |
| Frame rate                     | 25 fps  | Width   | 60.9 mm   |
| Video streaming                | ✓   | Height  | 57.9 mm   |
| Noise reduction                | ✓   | Length  | 138.8 mm  |
| Noise reduction technology     | 3D noise reduction  | Weight  | 175 g   |
| Image quality adjustment       | Brightness, Contrast, Saturation, Sharpness   | Packaging data                                |   |
| Bit rate control               | Constant Bit Rate (CBR)/Variable Bit Rate (VBR)                                     | Package width                                 | 163 mm  |
| Bit rate                       | 32 Kbps - 8 Mbps  | Package depth                                 | 75 mm   |
| Back Light Compensation (BLC)  | ✓   | Package height                                | 75 mm   |
| Highlight Compensation (HLC)   | ✓   | Package weight                                | 265 g   |
|                                |   | Sustainability                                |   |
|                                |   | Compliance certificates                       | CB, CE, Electromagnetic Compatibility (EMC), KC, Low Voltage Directive (LVD), REACH, RoHS, WEEE |
|                                |   | Packaging content                             |   |
|                                |   | Number of cameras *                           | 1   |
|                                |   | Technical details                             |   |
|                                |   | Lens mount interface                          | M12   |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date