## Samsung WA65D pizarrón interactivo 165.1 cm (65") 3840 x 2160 Pixeles Pantalla táctil Gris

Familia de productos: WAD Código del producto: Marca: Samsung

LH65WADWLGCXXY

## Nombre del producto:

WA65D

Samsung WA65D. Diagonal de la pantalla: 165.1 cm (65"), Brillo de pantalla: 400 cd / m², Resolución de la pantalla: 3840 x 2160 Pixeles. Sistema operativo instalado: Android, Memoria interna máxima: 64 GB. Micrófono: 3,5 mm. Color del producto: Gris, Interfaces de montaje de panel: 600 x 400 mm, Certificación: Part 15, Subpart B Class A KS C9832, KS C9835 EN55032:2015/A11:2020/A1:2020,EN 55035:2017/A11:2020.... Horas de funcionamiento (horas/días): 12/7





Display		Ports & interfaces	
Display diagonal *	165.1 cm (65")	RS-232 ports	2
Display brightness	400 cd/m²	IR input port	✓
Display resolution	3840 x 2160 pixels	Video out	Yes
HD type	4K Ultra HD	Ergonomics	
Panel type	ADS	Product colour	Grey
Native aspect ratio	16:9	VESA mounting	•
Contrast ratio (typical)	1200:1	Panel mounting interface	600 x 400 mm
Response time	8 ms		Part 15, Subpart B Class A KS C9832,
Touchscreen * Touch technology Touchscreen type Viewing angle, horizontal Viewing angle, vertical Pixel pitch Colour gamut Maximum pixel clock Haze rate Computer system Operating system installed Operating system version	Multi-touch Infrared 178° 178° 372 x 372 mm 72% 78 MHz 25%  Android 13	Certification	KS C9835 EN55032:2015/A11:2020/A1:2020,EN 55035:2017/A11:2020 EN 61000-3-2:2019/A1:2012 EN 61000-3-3:2013/A1:2019/A2:2021 EN 61000-3-2:2019/A1:2021 EN 61000-3-3:2013/A1:2019/A2:2021 EN 61000-3 IEC 62368-1 Edtion 3&IEC 60950-1 UL62368-1 edition 3 GB4943.1-2022 PSB+ IEC 62368-1 NOM-019 K 62368 IRAM+ IEC 62368-1 EAC+ IEC 62368-1 INMETRO+ IEC 62368-1 SASO+ IEC 62368-1 BSMI+ IEC 62368-1 IEC 62368-1/AS/NZS 62368-1 IEC60950-1 / IS13252
Maximum internal memory	64 GB	Performance	
Projector		Operating hours (hours/days)	12/7
Built-in projector *	×	Power	
Network		Power consumption (typical)	385 W
Wi-Fi	1	Power consumption (sleep)	0.5 W
Bluetooth	/	AC input voltage	100 - 240 V
Ethernet LAN		AC input frequency	50/60 Hz
	•	Operational conditions	
Ports & interfaces		Operating temperature (T-T)	0 - 40 °C
HDCP	✓	Operating relative humidity (H-H)	10 - 90%
HDCP version	2.1	Weight & dimensions	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A	4	Width *	1488 mm
ports quantity USB 2.0 ports quantity	1	Depth	88 mm
03b 2.0 ports qualitity	±	- op	

Ports & interfaces		Weight & dimensions	
HDMI ports quantity HDMI version Ethernet LAN (RJ-45) ports Microphone connectivity Audio output	3 2.0 2 3.5 mm 1	Height *	897 mm
		Weight	33.9 kg
		Bezel width	1.64 cm
		Packaging data	
		Package width	1628 mm
		Package depth	208 mm
		Package height	1024 mm
		Package weight	42.9 kg
		Quantity per pack	1 pc(s)

