


## BenQ LK935 Proyector de alcance estándar 5500 lúmenes ANSI DLP UHD 4K (3840x2160) 3D Blanco

Marca : BenQ Código del producto: 9H.JS277.14E

Nombre del producto: LK935







Projector		Ports & interfaces	
Smart projector * Screen size compatibility * Projector brightness * Projection technology * Projector native resolution * Contrast ratio (typical) * Native aspect ratio * Number of colours Vertical scan range 3D vertical scan range	X 3810 - 5080 mm (150 - 200") 5500 ANSI lumens DLP UHD 4K (3840x2160) 3000000:1 16:9 1.07 billion colours 15 - 135 Hz 23 - 240 Hz -30 - 30° -30 - 30° 92%	VGA (D-Sub) ports quantity * S/PDIF out port HDMI ports quantity * 3D sync port 3G-SDI input 3G-SDI output AC (power) in DC-in jack Audio Return Channel (ARC)	1  2  1  1  4  1  4  4  4  4  4  4
Keystone correction, horizontal Keystone correction, vertical Colour gamut		Network  Ethernet LAN *  Ethernet LAN (RJ-45) ports	<b>v</b> 1
Light source Light source type * Service life of light source * Service life of light source (economic mode)	Laser 20000 h 30000 h	Wi-Fi *  Features  HDCP  HDCP version	<b>x</b> ✓ 2.2
Lens system  Focal length range F-number (relative aperture) Zoom capability	8.6 - 9.4 mm 1.809	Multimedia  Built-in speaker(s) *  RMS rated power  Number of built-in speakers	<b>✓</b> 10 W 1
Zoom ratio Throw ratio Horizontal lens shift range Vertical lens shift range Offset	1.6:1 1.36 - 2.18 -23 - 23% -60 - 60% 0%	Design  Market positioning *  Product type *  Product colour *	Business Standard throw projector White

Video		Display	
Full HD *	✓	Built-in display *	×
3D *	✓	Power	
Supported graphics resolutions	640 x 480 (VGA), 3840 x 2160	Power source *	AC
HDMI connector type HDMI version HDBaseT port USB 2.0 ports quantity USB 2.0 Type-A ports quantity Audio (L/R) in * Audio (L/R) out Serial interface type *	Full-size 2.0b  ✓ 1 1 1 RS-232	Power consumption (typical) * Power consumption (standby) * Power consumption (max) AC input voltage AC input frequency Cord length	405 W
			0.5 W 520 W 100 - 240 V 50/60 Hz 1.8 m
		Operational conditions	
		Operating temperature (T-T)	0 - 40 °C
		Weight & dimensions	
		Width Depth Height Weight *	416 mm 351 mm 166 mm 7 kg
		Technical details	
		Image lag time	33.4 ms
		Other features	
		Security updates end date	31/12/2026





4718755091902

0840046048891



840046048891

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.