


Dienlay

BenQ RE7504 pantalla de señalización Panel plano interactivo 190.5 cm (75") 450 cd / m^2 4K Ultra HD Negro, Gris Pantalla táctil Procesador incorporado Android

Marca: BenQ Código del producto: RE7504

Nombre del producto: RE7504





Panel type PS Orientation Horizontal (Fig. 1975) Product colour* Blok, Grey (Fig. 1975) Blok (Fig. 1974) Blok (Fig. 1974) Blok (Fig. 1974) Pilet Pilet<	Display		Design	
Number of simultaneous touchpoints 40 Performance Education Native aspect ratio 16:9 Ambient light sensor ✓ Response time 8 ms Power Contrast ratio (typical) 1200:1 Power consumption (typical)* 73.9 W Contrast ratio (dynamic) 30000:1 Power consumption (standby)* 0.5 W Active display area (W x H) 1649.7 x 927.9 mm AC input voltage 100 - 240 V Panel life 50000 h AC input requency 50 - 60 Hz Surface hardness 9H AC input reguency 50 - 60 Hz RGB colour space NTSC Computer system ✓ Ports & interfaces Computer system ✓ HDMI ports quantity* 4 Built-in processor * ✓ HDMI input ports quantity 3 Processor architecture ARM Cortex-A53+Cortex-A73 HDMI input ports quantity 1 Internal memory 4 GB VGA (D-Sub) input ports 1 Op-bacing asphics card model ARM Mali-G52 DisplayPorts quantity* 1 Operating system insta	Display diagonal * Display resolution * Display brightness * HD type *	* 190.5 cm (75") 1 * 3840 x 2160 pixels s * 450 cd/m² 4K Ultra HD	Product colour * Screen shape VESA mounting * Panel mounting interface	Black, Grey Flat ✓ 800 x 400 mm
Fanel life Surface hardness 9H RGB colour space NTSC Computer system Computer system Compu	Number of simultaneous touchpoints Native aspect ratio Response time Contrast ratio (typical) Contrast ratio (dynamic)	40 16:9 8 ms 1200:1 30000:1	Performance Purpose * Ambient light sensor Power Power consumption (typical) * Power consumption (standby) *	Education 73.9 W 0.5 W
HDMI version 2.0 Processor architecture ARM Cortex-A53+Cortex-A73 HDMI input ports quantity 3 Processor cores 4 HDMI output ports quantity 1 Internal memory 4 GB VGA (D-Sub) input ports 1 1 On-board graphics card model ARM Mali-G52 DisplayPorts quantity 1 Internal storage capacity 64 GB DisplayPorts in 1 Operating system installed Android	Surface hardness RGB colour space	9H	AC input frequency Computer system	50 - 60 Hz
USB ports quantity USB version 2.0/3.2 Gen 1 (3.1 Gen 1) USB connector type USB Type-A, USB Type-B, USB Type- C Ethernet LAN * Ethernet LAN (RJ-45) ports 2 Ethernet LAN data rates 10,100,1000 Mbit/s Wi-Fi * Microphone in RS-232 interface Card reader integrated Display width 1716.5 mm 1716.5 mm Display depth 87.7 mm Display height 1041.6 mm Display weight 50 kg Packaging data Package width 180 mm 1800 mm Package depth 1860 mm Package weight 1120 mm Package weight Packaging content	HDMI version HDMI input ports quantity HDMI output ports quantity VGA (D-Sub) input ports DisplayPorts quantity * DisplayPorts in	2.0 3 1 1 1	Processor architecture Processor cores Internal memory On-board graphics card model Internal storage capacity Operating system installed	ARM Cortex-A53+Cortex-A73 4 4 GB ARM Mali-G52 64 GB Android
Ethernet LAN (RJ-45) ports 2 Ethernet LAN data rates 10,100,1000 Mbit/s Package width 180 mm Wi-Fi * Package depth 1860 mm Microphone in Package height 1120 mm RS-232 interface Package weight 65 kg Card reader integrated Package notent	USB ports quantity USB version USB connector type	8 2.0/3.2 Gen 1 (3.1 Gen 1) USB Type-A, USB Type-B, USB Type-C	Display width Display depth Display height	87.7 mm 1041.6 mm
Card reader integrated	Ethernet LAN (RJ-45) ports Ethernet LAN data rates Wi-Fi * Microphone in RS-232 interface	2 10,100,1000 Mbit/s ×	Package width Package depth Package height Package weight	1860 mm 1120 mm
	J	✓ MicroSD (TransFlash)		1

Decian

Ports & interfaces		Packaging content	
OPS module slot	✓	Stylus pen	✓
Audio		Number of stylus pens Cables included	2 HDMI, USB, VGA
Built-in speaker(s) * Number of built-in speakers	✓ 2 40 W	Mounting kit	IDINI, USB, VGA
RMS rated power		Operational conditions	
Design		Operating temperature (T-T)	0 - 40 °C
Product design * Placement supported *	Interactive flat panel Indoor	Operating relative humidity (H-H) Storage temperature (T-T) Storage relative humidity (H-H)	20 - 80% -10 - 60 °C 10 - 80%





840046050276

0840046050276

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.