



Dahua Technology Pro DH-SD60430UN-HNI cámara de vigilancia Esférico Cámara de seguridad IP Interior y exterior 2592 x 1520 Píxeles Techo/pared/Tubo

Marca : Dahua Technology

Familia de productos: Pro

Código del producto: DH-SD60430UN-HNI

Nombre del producto : DH-SD60430UN-HNI

Dahua Technology Pro DH-SD60430UN-HNI. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared/Tubo, Color del producto: Blanco, Factor de forma: Esférico. Iluminación mínima: 0.05 Lux, Ángulo de inclinación: -20 - 90°, Velocidad de preselección de la inclinación: 500 °/seg. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 3 mm (1 / 3"). Zoom digital: 16x, Distancia de detección: 2700 m, Distancia de observación: 1080 m

Performance		Video	
Type *	IP security camera		352 x 240, 352 x 288, 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2304 x 1296, 2592 x 1520
Placement supported *	Indoor & outdoor	Supported graphics resolutions	
Connectivity technology *	Wired	Noise reduction	✓
PTZ control	✓	Noise reduction technology	2D noise reduction, 3D noise reduction
PTZ modes	5 Pattern, 8 Tour, Auto scan, Auto pan	Gain control type	Auto/Manual
PTZ protocols	DH-SD, Pelco-P/D	Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Auto-tracking	✓	Bit rate	448K ~ 8192Kbps
Wide Dynamic Range (WDR)	✓	Back Light Compensation (BLC)	✓
Day/night mode	✓	Highlight Compensation (HLC)	✓
Alarm input/output	✓	Region of Interest (ROI) encoding	✓
Dynamic range	120 dB		
Design		Audio	
Form factor *	Spherical	Audio formats supported	AAC, G.711 A-law, G.722, G.726, G.729, MPEG-2
Mounting type *	Ceiling/Wall/Pole		
Product colour *	White	Network	
Housing material	Metal	Ethernet LAN *	✓
International Protection (IP) code	IP67	Ethernet interface type	Fast Ethernet
IK code	IK10	Supported network protocols	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS,PPPOE,DDNS,FTP, IP Filter,QoS,Bonjour,802.1x
Camera		Wi-Fi *	✗
Camera pan control	✓	Bluetooth *	✗
Camera tilt control	✓	Number of users	20 user(s)
Minimum illumination	0.05 lx	Streaming method	Multicast, Unicast
Tilt angle range	-20 - 90°	Storage	
Tilt preset speed	500 °/sec	Built-in HDD *	✗
Tilt manual speed	0.1 - 150 °/sec	ROM capacity	128 MB
Pan range	0 - 360°	RAM capacity	1024 MB
Pan preset speed	600 °/sec	Ports & interfaces	
Pan manual speed	0.1 - 300 °/sec	Ethernet LAN (RJ-45) ports	1
Auto flip	✓	RS-485 ports	1
White balance	ATW, Auto, Indoor, Manual, Outdoor	BNC output ports	1
Camera shutter type	Electronic	Security	
Camera shutter speed	1.1 - 1/30000 s	Alarm input channels	7
Number of Privacy masking areas	24	Alarm output channels	2
Image sensor			
Optical sensor size	25.4 / 3 mm (1 / 3")		
Progressive scan	✓		
Sensor type *	CMOS		

Lens system		Security	
Zoom capability	✓	Video motion detection	✓
Digital zoom	16x	Power	
Detect distance	2700 m	Power source type *	AC, PoE
Observe distance	1080 m	AC input voltage	24 V
Recognize distance	540 m	Power consumption (typical)	13 W
Focal length range	4.5 - 135 mm	Power consumption (max)	20 W
Auto focus	✓	DC output current	3 A
Maximum aperture number	4.4	Operational conditions	
Identify distance	270 m	Operating temperature (T-T)	-40 - 70 °C
Minimum aperture number	1.6	Operating relative humidity (H-H)	0 - 95%
Closest focusing distance	0.1 m	System requirements	
Video		Mobile operating systems supported	Android, iOS
Maximum resolution *	2592 x 1520 pixels	Weight & dimensions	
Total megapixels *	4 MP	Height	292 mm
Video compression formats	H.264, H.264+, H.265, H.265+, M-JPEG	Diameter	22.2 cm
		Weight	3.5 kg
		Packaging data	
		Package weight	7.5 kg
		Packaging content	
		Number of cameras *	1

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date