

GIGABYTE AORUS ELITE P850W unidad de fuente de alimentación
850 W 20+4 pin ATX ATX Negro

Marca : GIGABYTE

Código del producto: GP-AE850PM
PG5 EU

Nombre del producto : AORUS ELITE P850W Fuente de
Alimentación - PCIe 5.0, 80 PLUS Platinum, Diseño
completamente modular, Ventilador de 120 mm, Compatible
con ATX 3.0, Enchufe UE

- Listo para ATX 3.0 y PCIe Gen 5.0 (compatible con ATX 3.1)
- Certificado 80 PLUS Platinum
- Capacitores 100% japoneses
- Ventilador inteligente de rodamientos dinámicos de fluidos (FDB) de 120 mm
- Diseño compacto
- Diseño completamente modular
- Potente riel único de +12V
- Protección OVP/OPP/SCP/UVP/OCP/OTP
- Garantía de 10 años

AORUS ELITE P850W Fuente de Alimentación - PCIe 5.0, 80 PLUS Platinum, Diseño completamente
modular, Ventilador de 120 mm, Compatible con ATX 3.0, Enchufe UE

GIGABYTE AORUS ELITE P850W unidad de fuente de alimentación 850 W 20+4 pin ATX ATX Negro:

Asegure una entrega de energía confiable y eficiente con las fuentes de alimentación GIGABYTE.
Diseñadas para un rendimiento máximo y durabilidad, nuestras fuentes de alimentación ofrecen energía
estable y consistente para alimentar sus sistemas de alto rendimiento. Con protecciones avanzadas y
componentes de alta calidad, las fuentes de alimentación GIGABYTE brindan la confianza que necesita
para experiencias informáticas ininterrumpidas y sin problemas.

Power		Ports & interfaces	
Total power *	850 W	ATX power connector (20+4 pin)	✓
AC input voltage *	100 - 240 V	Floppy drive power connector	2
AC input frequency	50/60 Hz	Floppy disk drive connector	✓
Input current	12 A	PCI Express connector	✓
Power Factor Correction (PFC) type	Active	Cabling type	Fully-Modular
Combined power (+3.3V)	125 W	Performance	
Combined power (+12V)	849.6 W	80 PLUS certification *	80 PLUS Platinum
Combined power (+5V)	125 W	Purpose *	PC
Combined power (-12V)	3.6 W	Power supply unit (PSU) form factor *	ATX
Combined power (+5Vsb)	15 W	ATX version	3.1
Max output current (+3.3V)	25 A	Bearing technology	Ball bearing
Max output current (+12V)	70.8 A	Mean time between failures (MTBF)	100000 h
Max output current (+5V)	25 A	Design	
Max output current (-12V)	0.3 A	Product colour	Black
Max output current (+5Vsb)	3 A	Cooling type	Active
Hold time	16 ms	Fan diameter	12 cm
Efficiency	90%	Number of fans	1 fan(s)
Power Good signal delay range	100 - 150 ms	Fan location	Top
Power protection features	Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage	On/off switch	✓
Ports & interfaces		Weight & dimensions	
Motherboard power connector *	20+4 pin ATX	Width	150 mm
Motherboard power cable length	65 cm	Depth	140 mm
Number of SATA power connectors	8	Height	86 mm
Peripheral (Molex) power connectors (4-pin) *	4	Weight	2.67 kg
PCI Express power connectors (6+2 pin)	6	Packaging data	
		Package width	340 mm



Ports & interfaces		Packaging data	
CPU power connector (4+4 pin)	✓	Package depth	206 mm
		Package height	120 mm
		Package weight	3.3 kg
		Package type	Box
		Logistics data	
		Warranty period	10 year(s)



4719331554262

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 14-APR-2025. Prints or copies of Information are only valid on the printed Publication date