

GIGABYTE AORUS ELITE P850W ICE unidad de fuente de alimentación 850 W 20+4 pin ATX ATX Blanco

Marca : GIGABYTE

Código del producto: GP-AE850PM  
PG5 ICE EU

Nombre del producto : AORUS ELITE P850W ICE Fuente de Alimentación - PCIe 5.0, 80 PLUS Platinum, Diseño completamente modular, Ventilador de 120 mm, Compatible con ATX 3.0, Enchufe UE

- Compatible con ATX 3.0 y PCIe Gen 5.0 (compatible con ATX 3.1)
- Certificado 80 PLUS Platinum
- Capacitores 100% japoneses
- Ventilador de 120 mm con rodamiento de fluido dinámico inteligente (FDB)
- Diseño compacto
- Diseño totalmente modular
- Potente riel único de +12V
- Protección OVP/OPP/SCP/UVP/OC/OTP
- Garantía de 10 años

AORUS ELITE P850W ICE Fuente de Alimentación - PCIe 5.0, 80 PLUS Platinum, Diseño completamente modular, Ventilador de 120 mm, Compatible con ATX 3.0, Enchufe UE

GIGABYTE AORUS ELITE P850W ICE unidad de fuente de alimentación 850 W 20+4 pin ATX ATX Blanco:

Garantiza una entrega de energía fiable y eficiente con las fuentes de alimentación GIGABYTE. Diseñadas para un rendimiento óptimo y durabilidad, nuestras fuentes de alimentación ofrecen energía estable y consistente para alimentar tus sistemas de alto rendimiento. Con protecciones avanzadas y componentes de alta calidad, las fuentes de alimentación GIGABYTE brindan la confianza que necesitas para experiencias de computación ininterrumpidas y sin problemas.

| Power   |   | Ports & interfaces                    |                  |
|---|---|---------------------------------------|------------------|
| Total power *                                 | 850 W   | ATX power connector (20+4 pin)        | ✓                |
| AC input voltage *                            | 100 - 240 V   | Floppy drive power connector          | 2                |
| AC input frequency                            | 50/60 Hz  | Floppy disk drive connector           | ✓                |
| Input current                                 | 12 A  | PCI Express connector                 | ✓                |
| Power Factor Correction (PFC) type            | Active  | Cabling type                          | Fully-Modular    |
| Combined power (+3.3V)                        | 125 W   | Performance                           |                  |
| Combined power (+12V)                         | 849.6 W   | 80 PLUS certification *               | 80 PLUS Platinum |
| Combined power (+5V)                          | 125 W   | Purpose *                             | PC               |
| Combined power (-12V)                         | 3.6 W   | Power supply unit (PSU) form factor * | ATX              |
| Combined power (+5Vsb)                        | 15 W  | ATX version                           | 3.1              |
| Max output current (+3.3V)                    | 25 A  | Bearing technology                    | Ball bearing     |
| Max output current (+12V)                     | 70.8 A  | Mean time between failures (MTBF)     | 100000 h         |
| Max output current (+5V)                      | 25 A  | Design                                |                  |
| Max output current (-12V)                     | 0.3 A   | Product colour                        | White            |
| Max output current (+5Vsb)                    | 3 A   | Cooling type                          | Active           |
| Hold time                                     | 16 ms   | Fan diameter                          | 12 cm            |
| Efficiency                                    | 90%   | Number of fans                        | 1 fan(s)         |
| Power Good signal delay range                 | 100 - 150 ms  | Fan location                          | Top              |
| Power protection features                     | Over current, Over power, Over voltage, Overheating, Short circuit, Under voltage | On/off switch                         | ✓                |
|   |   | Weight & dimensions                   |                  |
| Ports & interfaces                            |   | Width                                 | 150 mm           |
| Motherboard power connector *                 | 20+4 pin ATX  | Depth                                 | 140 mm           |
| Motherboard power cable length                | 65 cm   | Height                                | 86 mm            |
| Number of SATA power connectors               | 8   | Weight                                | 2.68 kg          |
| Peripheral (Molex) power connectors (4-pin) * | 4   | Packaging data                        |                  |
| PCI Express power connectors (6+2 pin)        | 6   | Package width                         | 340 mm           |

| Ports & interfaces            |   | Packaging data    |            |
|-------------------------------|---|-------------------|------------|
| CPU power connector (4+4 pin) | ✓ | Package depth     | 206 mm     |
|                               |   | Package height    | 120 mm     |
|                               |   | Package weight    | 3.31 kg    |
|                               |   | Package type      | Box        |
|                               |   | Technical details |            |
|                               |   | Warranty period   | 10 year(s) |



4719331554392

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 10-JAN-2025. Prints or copies of Information are only valid on the printed Publication date