## GIGABYTE UD850GM PG5W unidad de fuente de alimentación 850 W 20+4 pin ATX ATX Blanco

Marca : GIGABYTE Código del producto: GP-UD850GM PG5W

Nombre del producto: UD850GM PG5W

Active PFC, 100-240 Vac, 12-6A, 60-50 Hz, 850W, 120mm Hydraulic Bearing(HYB)fan, 80 PLUS Gold GIGABYTE UD850GM PG5W. Potencia total: 850 W, Voltaje de entrada AC: 100 - 240 V, Corriente de entrada: 12 A. Alimentador de energía para tarjeta madre: 20+4 pin ATX, Longitud del cable de alimentación de la placa base: 61 cm, Longitud del cable de alimentación SATA: 150,300,450,600 mm. Utilizar con: PC, Factor de forma de fuente de alimentación (PSU): ATX, Certificación 80 PLUS: 80 PLUS Gold. Color del producto: Blanco, Tipo de enfriamiento: Activo, Diámetro de ventilador: 12 cm. Cables incluidos: CPU, PCIe, Peripheral (Molex), SATA





Power		Ports & interfaces	
Total power *	850 W	PCI Express power cable length	60 cm
AC input voltage *	100 - 240 V	CPU power connector (4+4 pin)	✓
Input current	12 A	CPU power cable length	60 cm
Power Factor Correction (PFC) type	Active	ATX power connector (20+4 pin)	/
Combined power (+3.3V)	105 W	Floppy drive power connector	1
Combined power (+12V)	732 W	Floppy disk drive connector	- -
Combined power (+5V)	105 W	Floppy disk drive cable length	15 cm
Combined power (-12V)	3.6 W	Cabling type	Fully-Modular
Combined power (+5Vsb)	15 W	5 7.	Tully-Modulal
Max output current (+3.3V)	20 A	Performance	
Max output current (+12V)	61 A	80 PLUS certification *	80 PLUS Gold
Max output current (+5V)	20 A	Purpose *	PC
Max output current (-12V)	2.3 A	Power supply unit (PSU) form factor	ATX
Max output current (+5Vsb)	3 A	*	
Hold time	16 ms	ATX version	2.31
Efficiency	90%	Bearing technology	HYB
	Over current, Over power, Over	Mean time between failures (MTBF)	100000 h
Power protection features	voltage, Overheating, Short circuit, Under voltage	Design	
Ports & interfaces		Product colour	White
		Cooling type	Active
Motherboard power connector *	20+4 pin ATX	Fan diameter	12 cm
Motherboard power cable length	61 cm	Number of fans	1 fan(s)
Number of SATA power connectors	8	Fan location	Тор
SATA power cable length	150,300,450,600 mm	On/off switch	✓
Peripheral (Molex) power connectors (4-pin) *	3	Packaging content	
Peripheral (Molex) power cable length	120,500 mm	Cables included	CPU, PCIe, Peripheral (Molex), SATA
EPS power connector (4+4 pin)	✓	Weight & dimensions	
. ,		Width	150 mm

Ports & interfaces	Weight & dimensions	
PCI Express power connectors (6+2 4	Depth	140 mm
pin)	Height	86 mm
	Logistics data	
	Harmonized System (HS) code	84733020

