

Dahua Technology DH-AS5500-24GT4XF-370 dispositivo de redes Gestionado L3 Gigabit Ethernet (10/100/1000) Energía sobre Ethernet (PoE) Negro

Marca : Dahua Technology

Código del producto: DHAS5500-24GT4XF-370

Nombre del producto: DH-AS5500-24GT4XF-370

Dahua Technology DH-AS5500-24GT4XF-370. Tipo de interruptor: Gestionado, Capa del interruptor: L3. Puertos tipo básico de conmutación RJ-45 Ethernet: Gigabit Ethernet (10/100/1000), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 24. Tabla de direcciones MAC: 16000 entradas, Capacidad de conmutación: 128 Gbit/s. Estándares de red: IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z. Energía sobre Ethernet (PoE). Montaje en rack

Management features		Power	
Switch type * Switch layer Web-based management System event log	Managed L3 ✓	Power source * Power supply included * AC input voltage AC input frequency	AC ✓ 100 - 240 V 50/60 Hz
Ports & interfaces		Input current	8 A
Basic switching RJ-45 Ethernet ports quantity *	24	Power consumption (typical) Power consumption (max)	24 W 451 W
Basic switching RJ-45 Ethernet ports	Gigabit Ethernet (10/100/1000)	Power over Ethernet (PoE)	
type * SFP+ module slots quantity	4	Power over Ethernet (PoE) *	✓
Network		Power over Ethernet (PoE) power per port	30 W
Networking standards *	IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3ae, IEEE 802.3u,	Total Power over Ethernet (PoE) budget	370 W
100	IEEE 802.3x, IEEE 802.3z	Operational conditions	
10G support * Data transmission Switching capacity * Forwarding rate	128 Gbit/s 95.232 Mpps	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-5 - 45 °C -40 - 70 °C 5 - 95% 5 - 95%
MAC address table *	16000 entries	Weight & dimensions	
Jumbo frames support Jumbo frames Packet buffer memory Security	10000 12 MB	Width Depth Height Weight	440 mm 260 mm 43.6 mm 4.75 kg
IGMP snooping	/	Packaging data	-
Multicast features Multicast support	✓	Package width Package depth	556 mm 430 mm
Protocols		Package height Package weight	156 mm 5.8 kg
	Load update files and update using Xmodem/FTP/TFTP Configure through CLI, Telnet, and Console port SNMPv1/v2/v3 Web network management RMON alarm, RMON	Certificates	3.0 kg
Management protocols		Certification	CE; FCC
Supported network protocols	STP/RSTP/MSTP PVST RRPP ERPS		
Design			
Rack mounting *	/		

Design

Stackable *

Product colour

Housing material

Metal

