



Dahua Technology WizSense IPC-HDW2549T-S-PV Torreta Cámara de seguridad IP Interior y exterior 2960 x 1688 Pixeles Techo

Marca : Dahua Technology

Familia de productos:
WizSense

Código del producto: DH-IPC-HDW2549T-S-PV

Nombre del producto : IPC-HDW2549T-S-PV

Dahua Technology WizSense IPC-HDW2549T-S-PV. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo, Color del producto: Blanco, Factor de forma: Torreta. Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 111°, Ángulo de visión del objetivo, vertical: 58.5°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.7 mm (1 / 2.7"). Intervalo de longitud focal: 2.8, 3.6 mm, Distancia de identificación: 6.4 m, Distancia de detección (angular): 63.8 m

Performance		Video	
Type *	IP security camera	Video streaming	✓
Placement supported *	Indoor & outdoor	Noise reduction	✓
Connectivity technology *	Wired	Noise reduction technology	3D noise reduction
Wide Dynamic Range (WDR)	✓	Gain control type	Auto/Manual
Day/night mode	✓	Privacy masking	✓
Certification	CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU	Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Design		Bit rate	32 Kbps - 8192 Kbps
Form factor *	Turret	Back Light Compensation (BLC)	✓
Mounting type *	Ceiling	Highlight Compensation (HLC)	✓
Product colour *	White	Region of Interest (ROI) encoding	✓
Housing material	Metal, Plastic	Smart IR	✓
International Protection (IP) code	IP67	Audio	
Camera		Signal-to-Noise Ratio (SNR)	56 dB
Camera pan control	✓	Network	
Camera tilt control	✓	Ethernet LAN *	✓
Minimum illumination	0 lx	Ethernet interface type	Fast Ethernet
Angle of rotation	360°	Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP ; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; P2P; PPPoE; Bonjour; auto registration
Lens viewing angle, horizontal	111°		
Lens viewing angle, vertical	58.5°		
Lens viewing angle, diagonal	136°		
Tilt angle range	0 - 78°	Wi-Fi *	✗
Pan range	0 - 360°	Bluetooth *	✗
White balance	Auto, Manual, Natural, Outdoor, Regional custom, Street lamp	Number of users	20 user(s)
Camera shutter type	Electronic	Quality of Service (QoS) support	✓
Camera shutter speed	1/3 - 1/100000 s	Streaming method	Multicast
Adjustment shutter speed	Auto/Manual	Storage	
Image sensor		Built-in HDD *	✗
Number of sensors	1	Compatible memory cards	MicroSD (TransFlash)
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	Maximum memory card size	256 GB
Progressive scan	✓	ROM capacity	128 MB
Sensor type *	CMOS	Ports & interfaces	
Lens system		Ethernet LAN (RJ-45) ports	1
Number of lenses *	1	Security	
Focal length range	2.8, 3.6 mm	Video motion detection	✓
Maximum aperture number	1	Active tampering alarm	✓
Identify distance	6.4 m		
Detect distance (wide)	63.8 m		

Lens system		Security	
Detect distance (tele)	77.8 m	Intelligent Video Surveillance (IVS) system features	Intrusion, Tripwire
Observe distance (wide)	25.5 m	Mirror	✓
Observe distance (tele)	31.1 m	Management features	
Recognize distance (wide)	12.8 m	Web browser	✓
Recognize distance (tele)	15.6 m	Power	
Identify distance (wide)	6.4 m	Power source type *	DC, PoE
Identify distance (tele)	7.8 m	Power consumption (typical)	2.2 W
Night vision		DC output voltage	12
Night vision *	✓	Operational conditions	
Night vision distance	30 m	Operating temperature (T-T)	-40 - 60 °C
LED type	IR/White	Storage temperature (T-T)	-40 - 60 °C
Number of illumination LEDs	2	Operating relative humidity (H-H)	0 - 95%
Video		System requirements	
Maximum resolution *	2960 x 1688 pixels	Mobile operating systems supported	Android, iOS
Total megapixels *	5 MP	Weight & dimensions	
Video compression formats	H.264, H.264B, H.264H, H.265, M-JPEG	Diameter	11 cm
Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2048 x 1536 (QXGA), 2304 x 1296, 2688 x 1520, 2880 x 1620	Length	103.5 mm
		Weight	390 g
Supported video modes	720p, 1080p	Packaging data	
Frame rate	30 fps	Package weight	570 g
		Packaging content	
		Number of cameras *	1

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-FEB-2025. Prints or copies of Information are only valid on the printed Publication date