



Dahua Technology WizSense IPC-HDW2549T-S-PV Torreta Cámara de seguridad IP Interior y exterior 2960 x 1688 Pixeles Techo

Marca : Dahua Technology

Familia de productos: WizSense

Código del producto: DH-IPC-HDW2549T-S-PV

Nombre del producto : IPC-HDW2549T-S-PV

Dahua Technology WizSense IPC-HDW2549T-S-PV. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo, Color del producto: Blanco, Factor de forma: Torreta. Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 111°, Ángulo de visión del objetivo, vertical: 58.5°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.7 mm (1 / 2.7"). Intervalo de longitud focal: 2.8, 3.6 mm, Distancia de identificación: 6.4 m, Distancia de detección (angular): 63.8 m

| Performance | | Video | |
|------------------------------------|---|-----------------------------------|---|
| Type * | IP security camera | Video streaming | ✓ |
| Placement supported * | Indoor & outdoor | Noise reduction | ✓ |
| Connectivity technology * | Wired | Noise reduction technology | 3D noise reduction |
| Wide Dynamic Range (WDR) | ✓ | Gain control type | Auto/Manual |
| Day/night mode | ✓ | Privacy masking | ✓ |
| Certification | CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU | Bit rate control | Constant Bit Rate (CBR)/Variable Bit Rate (VBR) |
| Design | | Bit rate | 32 Kbps - 8192 Kbps |
| Form factor * | Turret | Back Light Compensation (BLC) | ✓ |
| Mounting type * | Ceiling | Highlight Compensation (HLC) | ✓ |
| Product colour * | White | Region of Interest (ROI) encoding | ✓ |
| Housing material | Metal, Plastic | Smart IR | ✓ |
| International Protection (IP) code | IP67 | Audio | |
| Camera | | Signal-to-Noise Ratio (SNR) | 56 dB |
| Camera pan control | ✓ | Network | |
| Camera tilt control | ✓ | Ethernet LAN * | ✓ |
| Minimum illumination | 0 lx | Ethernet interface type | Fast Ethernet |
| Angle of rotation | 360° | Supported network protocols | IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP ; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; P2P; PPPoE; Bonjour; auto registration |
| Lens viewing angle, horizontal | 111° | | |
| Lens viewing angle, vertical | 58.5° | Wi-Fi * | ✗ |
| Lens viewing angle, diagonal | 136° | Bluetooth * | ✗ |
| Tilt angle range | 0 - 78° | Number of users | 20 user(s) |
| Pan range | 0 - 360° | Quality of Service (QoS) support | ✓ |
| White balance | Auto, Manual, Natural, Outdoor, Regional custom, Street lamp | Streaming method | Multicast |
| Camera shutter type | Electronic | Storage | |
| Camera shutter speed | 1/3 - 1/100000 s | Built-in HDD * | ✗ |
| Adjustment shutter speed | Auto/Manual | Compatible memory cards | MicroSD (TransFlash) |
| Image sensor | | Maximum memory card size | 256 GB |
| Number of sensors | 1 | ROM capacity | 128 MB |
| Optical sensor size | 25.4 / 2.7 mm (1 / 2.7") | Ports & interfaces | |
| Progressive scan | ✓ | Ethernet LAN (RJ-45) ports | 1 |
| Sensor type * | CMOS | Security | |
| Lens system | | Video motion detection | ✓ |
| Number of lenses * | 1 | Active tampering alarm | ✓ |
| Focal length range | 2.8, 3.6 mm | | |
| Maximum aperture number | 1 | | |
| Identify distance | 6.4 m | | |
| Detect distance (wide) | 63.8 m | | |

| | | | |
|--------------------------------|--|--|---------------------|
| Lens system | | Security | |
| Detect distance (tele) | 77.8 m | Intelligent Video Surveillance (IVS) system features | Intrusion, Tripwire |
| Observe distance (wide) | 25.5 m | Mirror | ✓ |
| Observe distance (tele) | 31.1 m | Management features | |
| Recognize distance (wide) | 12.8 m | Web browser | ✓ |
| Recognize distance (tele) | 15.6 m | Power | |
| Identify distance (wide) | 6.4 m | Power source type * | DC, PoE |
| Identify distance (tele) | 7.8 m | Power consumption (typical) | 2.2 W |
| Night vision | | DC output voltage | 12 |
| Night vision * | ✓ | Operational conditions | |
| Night vision distance | 30 m | Operating temperature (T-T) | -40 - 60 °C |
| LED type | IR/White | Storage temperature (T-T) | -40 - 60 °C |
| Number of illumination LEDs | 2 | Operating relative humidity (H-H) | 0 - 95% |
| Video | | System requirements | |
| Maximum resolution * | 2960 x 1688 pixels | Mobile operating systems supported | Android, iOS |
| Total megapixels * | 5 MP | Weight & dimensions | |
| Video compression formats | H.264, H.264B, H.264H, H.265, M-JPEG | Diameter | 11 cm |
| Supported graphics resolutions | 352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2048 x 1536 (QXGA), 2304 x 1296, 2688 x 1520, 2880 x 1620 | Length | 103.5 mm |
| Supported video modes | 720p, 1080p | Weight | 390 g |
| Frame rate | 30 fps | Packaging data | |
| | | Package weight | 570 g |
| | | Packaging content | |
| | | Number of cameras * | 1 |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date