



Dahua Technology WizMind IPC-HDBW5441E-ZE-HDMI Domo Cámara de seguridad IP Interior y exterior 2688 x 1520 Píxeles Techo

Marca : Dahua Technology

Familia de productos:
WizMind

Código del producto: DH-IPC-
HDBW5441E-ZE-HDMI

Nombre del producto : IPC-
HDBW5441E-ZE-HDMI

Dahua Technology WizMind IPC-HDBW5441E-ZE-HDMI. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo, Color del producto: Negro, Blanco, Factor de forma: Domo. Iluminación mínima: 0.002 Lux, Ángulo de rotación: 355°, Ángulo de inclinación: 0 - 65°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.9 mm (1 / 2.9"). Intervalo de longitud focal: 2.7 - 13.5 mm, Distancia de identificación: 6.4 m, Distancia de detección (angular): 64 m

Performance		Video	
Type *	IP security camera	Video compression formats	H.264, H.264B, H.264H, H.265, M-JPEG
Placement supported *	Indoor & outdoor		352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2048 x 1536 (QXGA), 2304 x 1296, 2560 x 1440, 2688 x 1520
Connectivity technology *	Wired		
PTZ control	✓	Supported graphics resolutions	
Wide Dynamic Range (WDR)	✓		
Day/night mode	✓		
Certification	CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU	Frame rate	30 fps
Design		Video streaming	✓
Form factor *	Dome	Noise reduction	✓
Mounting type *	Ceiling	Noise reduction technology	3D noise reduction
Product colour *	Black, White	Gain control type	Auto/Manual
International Protection (IP) code	IP67	Privacy masking	✓
IK code	IK10	Bit rate control	Constant Bit Rate (CBR), Variable Bit Rate (VBR)
Camera		Bit rate	H.264: 3 kbps-16384 kbps; H.265: 3 kbps-16384 kbps
Camera pan control	✓	Back Light Compensation (BLC)	✓
Camera tilt control	✓	Highlight Compensation (HLC)	✓
Minimum illumination	0.002 lx	Audio	
Angle of rotation	355°	Signal-to-Noise Ratio (SNR)	56 dB
Tilt angle range	0 - 65°	Built-in microphone	✓
Pan range	0 - 355°	Voice codecs	G.711Mu, G.711a, G.723, G.726, PCM
White balance	Auto, Manual, Natural, Outdoor, Regional custom, Street lamp	Network	
Camera shutter type	Electronic	Ethernet LAN *	✓
Camera shutter speed	1/3 - 1/100000 s	Ethernet interface type	Fast Ethernet
Image sensor		Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; PPPoE; SNMP; P2P
Optical sensor size	25.4 / 2.9 mm (1 / 2.9")		
Progressive scan	✓		
Sensor type *	CMOS	Storage	
Lens system		ROM capacity	256 MB
Number of lenses *	1	RAM capacity	1000 MB
Focal length range	2.7 - 13.5 mm	Ports & interfaces	
Maximum aperture number	1.6	Ethernet LAN (RJ-45) ports	1
Identify distance	6.4 m	Security	
Detect distance (wide)	64 m	Motion sensor	✓
Detect distance (tele)	210 m		
Observe distance (wide)	25.6 m		
Observe distance (tele)	84 m		

Lens system		Security	
Recognize distance (wide)	12.8 m	Mirror	✓
Recognize distance (tele)	42 m	Management features	
Identify distance (wide)	6.4 m	Web browser	✓
Identify distance (tele)	21 m	Management software	Smart PSS; DSS; DMSS
Closest focusing distance	0.1 m	Power	
Night vision		Power source type *	DC, PoC
Night vision *	✓	Power consumption (typical)	3.6 W
Night vision distance	40 m	Power consumption (Power over Ethernet (PoE))	4.7 W
LED type	IR	DC output voltage	12
Number of illumination LEDs	3	Operational conditions	
Video		Operating temperature (T-T)	-30 - 60 °C
Maximum resolution *	2688 x 1520 pixels	Storage temperature (T-T)	-40 - 60 °C
Total megapixels *	4 MP	Operating relative humidity (H-H)	0 - 95%
		Weight & dimensions	
		Height	118.1 mm
		Diameter	15.9 cm
		Weight	920 g
		Packaging data	
		Package weight	1.22 kg
		Packaging content	
		Number of cameras *	1

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-FEB-2025. Prints or copies of Information are only valid on the printed Publication date