



Dahua Technology WizSense SD2A300NB-GNY-A-PV Tower Cámara de seguridad IP Exterior 2560 x 1920 Píxeles Techo/pared

Marca : Dahua Technology

Familia de productos: WizSense

Código del producto: DH-SD2A300NB-GNY-A-PV

Nombre del producto : SD2A300NB-GNY-A-PV

Dahua Technology WizSense SD2A300NB-GNY-A-PV. Tipo: Cámara de seguridad IP, Colocación compatible: Exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared, Color del producto: Blanco, Factor de forma: Tower. Ángulo de visión del objetivo, horizontal: 80.4°, Ángulo de visión del objetivo, vertical: 58.1°, Ángulo de visión de la lente, diagonal: 104.8°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.8 mm (1 / 2.8"). Distancia de detección: 77.4 m, Distancia de observación: 31 m, Distancia de reconocimiento: 15.5 m



| Performance | | Night vision | |
|------------------------------------|--------------------|-----------------------------|----------------------|
| Type * | IP security camera | Night vision distance | 30 m |
| Placement supported * | Outdoor | B/W night vision distance | 30 m |
| Connectivity technology * | Wired | LED type | IR/White |
| PTZ control | ✓ | Number of illumination LEDs | 4 |
| PTZ modes | Preset point | Video | |
| Day/night mode | ✓ | Maximum resolution * | 2560 x 1920 pixels |
| Alarm input/output | ✓ | Total megapixels * | 5 MP |
| Built-in light | ✓ | Audio | |
| Design | | Built-in speaker(s) | ✓ |
| Form factor * | Tower | Audio system | 1-way |
| Mounting type * | Ceiling/wall | Audio input channels | 1 channels |
| Product colour * | White | Audio output channels | 1 channels |
| International Protection (IP) code | IP66 | Built-in microphone | ✓ |
| Weatherproof | ✓ | Number of microphones | 1 |
| Camera | | Network | |
| Camera pan control | ✓ | Ethernet LAN * | ✓ |
| Camera tilt control | ✓ | Storage | |
| Minimum illumination | 0 lx | Built-in HDD * | ✗ |
| Lens viewing angle, horizontal | 80.4° | Card reader integrated | ✓ |
| Lens viewing angle, vertical | 58.1° | Compatible memory cards | MicroSD (TransFlash) |
| Lens viewing angle, diagonal | 104.8° | ROM capacity | 128 MB |
| Tilt angle range | 0 - 80° | RAM capacity | 128 MB |
| Tilt preset speed | 36.3 °/sec | Ports & interfaces | |
| Tilt manual speed | 0.1 - 36.4 °/sec | Ethernet LAN (RJ-45) ports | 1 |
| Pan preset speed | 74 °/sec | | |
| Pan manual speed | 0.1 - 36.4 °/sec | | |

| Image sensor | | Security | |
|---------------------|--------------------------|-----------------------|----------|
| Optical sensor size | 25.4 / 2.8 mm (1 / 2.8") | Alarm input channels | 1 |
| Progressive scan | ✓ | Alarm output channels | 1 |
| Sensor type * | CMOS | Siren noise level | 55 dB |
| Lens system | | Management features | |
| Detect distance | 77.4 m | Web-based management | ✓ |
| Observe distance | 31 m | Power | |
| Recognize distance | 15.5 m | Power source type * | PoE |
| Lens diameter | 7.74 mm | Weight & dimensions | |
| Night vision | | Width | 140.5 mm |
| Night vision * | ✓ | Diameter | 11.1 cm |
| | | Weight | 500 g |
| | | Weight (with stand) | 1 kg |
| | | Packaging content | |
| | | Number of cameras * | 1 |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-FEB-2025. Prints or copies of Information are only valid on the printed Publication date