

## Dahua Technology DHI-ASI3203E lector de control de acceso Lector de control de acceso básico Negro

Marca : Dahua Technology Código del producto: DHI-ASI3203E

Nombre del producto : DHI-ASI3203E

Dahua Technology DHI-ASI3203E. Diagonal de la pantalla: 6.1 cm (2.4"), Máxima resolución: 320 x 240 Pixeles, Forma de la pantalla: Plana. Tipo de cámara frontal: Cámara doble, Tipo de sensor: CMOS, Total de megapixeles: 2 MP. Protocolos de red compatibles: IPv4;RTSP;UDP;P2P;IPv6;RTP;TCP. Voltaje de entrada: 12 V, Corriente de entrada: 2 A, Consumo energético: 12 W. Ancho: 184.9 mm, Profundidad: 76.2 mm, Altura: 20.5 mm

Technical details		Ports & interfaces	
Type *  Authentication type *  Fingerprint reader *  Access code reader *	recognition, Password  nt reader *  de reader *  vip/card reader *  dection  decity  gnition distance  recognition, Password  X  1000  1000  1.2 - 2 m	Ethernet LAN (RJ-45) ports Supported network protocols PC connected * RS-485 ports USB port	1 IPv4;RTSP;UDP;P2P;IPv6;RTP;TCP ✓ 1
Access chip/card reader *  Alarm function  Face capacity  Face recognition distance  Face recognition accuracy		Power Input voltage Input current Power consumption (typical)	12 V 2 A 12 W
ser capacity 1000 user(s) assword capacity 1000	Weight & dimensions Width	184.9 mm	
Record capacity Product colour Housing material	100000 Black Acrylonitrile butadiene styrene (ABS), Polycarbonate (PC)	Depth Height Weight	76.2 mm 20.5 mm 600 g
Display	(ABS), Folycarbonate (FC)	Packaging data	219 mm
Built-in display * Display diagonal	<b>√</b> 6.1 cm (2.4")	Package width Package depth Package height	122 mm 58 mm
Maximum resolution Screen shape	320 x 240 pixels Flat	Operational conditions	
Touchscreen	X	Operating temperature (T-T) Operating relative humidity (H-H)	-10 - 45 °C 0 - 90%
Camera		Storage temperature (T-T)	-20 - 70 °C
Front camera * Front camera type Sensor type Total megapixels Wide Dynamic Range (WDR)	✓ Dual camera CMOS 2 MP	Storage relative humidity (H-H)	30 - 75%

