

Dahua Technology IS4210-8GT-120 Gestionado L2 Gigabit Ethernet (10/100/1000) Energía sobre Ethernet (PoE) Negro

Marca: Dahua Technology Código del producto: DH-IS4210-8GT-120

Nombre del producto: IS4210-8GT-120

Dahua Technology IS4210-8GT-120. Tipo de interruptor: Gestionado, Capa del interruptor: L2. Puertos tipo básico de conmutación RJ-45 Ethernet: Gigabit Ethernet (10/100/1000), Cantidad de puertos básicos de conmutación RJ-45 Ethernet: 8. Tipo de switch o conmutador óptico: Gigabit Ethernet. Puerto de consola: RJ-45. Bidireccional completo (Full duplex). Tabla de direcciones MAC: 8000 entradas, Capacidad de conmutación: 20 Gbit/s. Estándares de red: IEEE 802.3, IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3at, IEEE 802.3bt, IEEE 802.3u,.... Voltaje de entrada DC: 53 V. Energía sobre Ethernet (PoE)

Management features		Design	
Switch type *	Managed	Rack mounting *	×
Switch layer	L2	Product colour	Black
Ports & interfaces		Reset button	✓
Basic switching RJ-45 Ethernet ports	8	Performance	
quantity * Basic switching RJ-45 Ethernet ports		Mean time between failures (MTBF)	1198177.29 h
type *	Gigabit Ethernet (10/100/1000)	Power	
Gigabit Ethernet (copper) ports quantity	8	Power source *	AC
SFP module slots quantity	2	Power supply included *	×
Console port	RJ-45	DC input voltage	53 V
Network	,	Power consumption (max)	120 W
Network	IEEE 802.3, IEEE 802.3ab, IEEE	Power over Ethernet (PoE)	
Networking standards *	802.3ad, IEEE 802.3af, IEEE	Power over Ethernet (PoE) *	✓
Networking standards	802.3at, IEEE 802.3bt, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z	Power over Ethernet (PoE) ports quantity	8
10G support *	×	Power over Ethernet (PoE) power	30 W
Full duplex	✓	per port	30
Flow control support	✓	Total Power over Ethernet (PoE) budget	120 W
Link aggregation	1	Operational conditions	
Ethernet Ring Protection Switching (ERPS)	✓	Operating temperature (T-T)	-40 - 75 °C
VLAN support	/	Operating relative humidity (H-H)	5 - 95%
Number of VLANs	4000	Weight & dimensions	
Optical fiber		Width	53.5 mm
Switching optical modules type	Gigabit Ethernet	Depth	125 mm
Data transmission		Height	175 mm
Switching capacity *	20 Gbit/s	Weight	1.25 kg
Forwarding rate	14.88 Mpps	Packaging data	
MAC address table *	8000 entries	Package width	287 mm
		Package depth	254
Jumbo frames support	✓	rackage deptil	254 mm
Jumbo frames support Jumbo frames	10000	Package height	101 mm
		•	
Jumbo frames	10000	Package height	101 mm
Jumbo frames Packet buffer memory	10000	Package height Package weight	101 mm
Jumbo frames Packet buffer memory Security	10000 4.1 MB	Package height Package weight Sustainability	101 mm 1.52 kg
Jumbo frames Packet buffer memory Security DHCP features	10000 4.1 MB DHCP client	Package height Package weight Sustainability Sustainability compliance	101 mm 1.52 kg

