

Dahua Technology DH-AS5500-48GF4XF dispositivo de redes Gestionado L3 Negro

Marca: Dahua Technology Código del producto: DH-AS5500-48GF4XF

Nombre del producto: DH-AS5500-48GF4XF

Dahua Technology DH-AS5500-48GF4XF. Tipo de interruptor: Gestionado, Capa del interruptor: L3. Tabla de direcciones MAC: 16000 entradas, Capacidad de conmutación: 176 Gbit/s. Estándares de red: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3x. Montaje en rack

Management features		Power	
Switch type * Switch layer Web-based management	Managed L3 ✓	Power source * Power supply included * AC input voltage	AC ✓ 100 - 240 V
System event log	✓	AC input frequency	50/60 Hz
Ports & interfaces		Input current	2.5 A
Basic switching RJ-45 Ethernet ports type *	×	Power over Ethernet (PoE) Power over Ethernet (PoE) *	×
SFP module slots quantity	48	. ,	^
Network		Operational conditions Operating temperature (T-T)	-5 - 45 °C
Networking standards *	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1s, IEEE 802.1w, IEEE 802.3ad, IEEE 802.3x	Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	-40 - 70 °C 5 - 95% 5 - 95%
Data transmission		Weight & dimensions	
Switching capacity * Forwarding rate MAC address table * Jumbo frames support Jumbo frames	176 Gbit/s 130.952 Mpps 16000 entries ✓ 10000	Width Depth Height Weight	440 mm 360 mm 43.6 mm 6.5 kg
Packet buffer memory	24 MB	Packaging data	
Security		Package width	562 mm
IGMP snooping	✓	Package depth Package height	550 mm 125 mm
Protocols		Package weight	7 kg
Management protocols	Load update files and update using FTP Configure through CLI, Telnet, and Console port SNMPv1/v2/v3 NTP Ping and Tracert LLDP Port loopback detection	Certificates	
			CE; FCC
Supported network protocols	STP/RSTP/MSTP PVST RRPP		
Design			
Rack mounting *	✓		
Stackable *	✓		
Product colour	Black		
Housing material	Metal		

