

DELL PowerEdge T560 servidor 480 GB Torre (4.5U) Intel® Xeon Silver 4410Y 2 GHz 16 GB DDR5-SDRAM 800 W

Marca : DELL Familia de productos: Código del producto: T560-PowerEdge FY25Q3-MX

Nombre del producto: T560

- No OS

- Intel Xeon Silver 4410Y (30MB Cache, 2GHz)

- 16GB DDR5-SDRAM & 480GB SSD

- iDRAC9, Enterprise 16G

Intel Xeon Silver 4410Y (30MB Cache, 2GHz), 16GB DDR5-SDRAM, 480GB SSD, LAN (Broadcom 5720), PERC H755, iDRAC9, Enterprise 16G, $2 \times 800W$, No OS

DELL PowerEdge T560. Familia de procesador: Intel® Xeon Silver, Frecuencia del procesador: 2 GHz, Modelo del procesador: 4410Y. Memoria interna: 16 GB, Tipo de memoria interna: DDR5-SDRAM. Capacidad total de almacenaje: 480 GB. Ethernet, Tecnología de cableado: 10/100/1000Base-T(X). Fuente de alimentación: 800 W, Suministro de energía redundante (RPS), soporte. Tipo de chasis: Torre (4.5U)





Processor		Ports & interfaces	
Processor manufacturer * Intel Processor family * Intel Xeon Silver Processor generation Intel Xeon Scalable 4th Gen Processor model * 4410Y Processor frequency * 2 GHz	Ethernet LAN (RJ-45) ports * USB 2.0 ports quantity USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity VGA (D-Sub) ports quantity	2 2 2 1	
Processor boost frequency	3.9 GHz	Design	
Processor cores Processor cache	12 30 MB	Chassis type * Product colour	Tower (4.5U) Black
Motherboard chipset Number of processors installed	Intel C741	Performance	
Thermal Design Power (TDP)	150 W	Remote administration	iDRAC9, Enterprise 16G
System bus rate	16 GT/s	Software	
Processor threads	24	Operating system installed *	×
Memory types supported by processor Memory clock speeds supported by processor Memory	DDR5-SDRAM 4000 MHz	Compatible operating systems *	Canonical® Ubuntu® Server LTS Microsoft® Windows Server® with Hyper-V RedHat® Enterprise Linux SUSE® Linux Enterprise Server VMware® ESXi®
Internal memory *	16 GB	Power	
Internal memory type * Buffered memory type	DDR5-SDRAM Registered (buffered)	Redundant power supply (RPS) support *	✓
Memory ranking	1	Power supply *	800 W
Memory slots	16x DIMM	Number of redundant power supplies supported	2
Memory data transfer rate Maximum internal memory *	4800 MT/s 1 TB	Number of redundant power supplies installed	2
Storage		Power cable connector 1	NEMA 5-15P
Total storage capacity *	480 GB	Power cable connector 2	C13 coupler
Number of SSDs installed SSD capacity	1 480 GB	Carbon footprint	

Storage		Carbon footprint	
SSD interface	SATA III	Total carbon footprint (kg of CO2e)	5989
SSD size Supported SSD sizes	2.5" 3.5"	Total carbon emissions, standard deviation (kg of CO2e)	3189
Number of SSDs supported	8	Carbon emissions, manufacturing (kg of CO2e)	419
RAID support * Supported RAID controllers	✓ PERC H755	Carbon emissions, logistics (kg of CO2e)	299
Hot-Plug support Optical drive type *	×	Carbon emissions, energy usage (kg of CO2e)	5210
Drive writes per day (DWPD)	3	Carbon emissions, end-of-life (kg of CO2e)	60
Storage drive adapter included Storage drive adapter type	✓ 2.5" - 3.5"	Total carbon emissions, w/o use phase (kg of CO2e)	779
Network		PAIA version	1.3.2, 2022
LAN controller	Broadcom 5720	Weight & dimensions	
Ethernet LAN	✓	Width	200 mm
Cabling technology Ethernet interface type	10/100/1000Base-T(X) Gigabit Ethernet	Other features	
		Data transfer rate Bytes per sector Open Compute Project (OCP)	6 Gbit/s 512 NIC 3.0

