



BenQ ST6502S Pantalla plana de señalización digital 165.1 cm (65") LCD 400 cd / m² 4K Ultra HD Negro Procesador incorporado

Marca : BenQ Código del producto: 9H.F88PT.DA4

Nombre del producto: ST6502S







Display		Performance	
Panel type	PLS	Purpose *	Corporate
Display diagonal *		Power	
Display technology * LCD Display resolution * 3840 x 2160 pixels Display brightness * 400 cd/m² HD type * 4K Ultra HD Touchscreen * X Dative aspect ratio 16:9 Response time 8 ms Contrast ratio (typical) 1200:1 Rective display area (W x H) 1428.5 x 803.5 mm	Power consumption (typical) * Power consumption (standby) * Input voltage Energy efficiency class (SDR) Energy consumption (SDR) per 1000 hours AC input voltage AC input frequency Energy efficiency scale	155 W 0.5 W 100 - 240 V G 155 kWh 100 - 240 V 50 - 60 Hz A to G	
Panel life	30000 h	Computer system	
RGB colour space	NTSC	Computer system *	✓
Ports & interfaces HDMI ports quantity * HDMI version HDMI input ports quantity DVI port * VGA (D-Sub) input ports	* 3 2.0 antity 3	Built-in processor * Processor architecture Processor cores Internal memory On-board graphics card model Internal storage capacity	ARM Cortex-A53+Cortex-A73 4 3 GB ARM Mali-G51 MP2 16 GB
USB port * USB ports quantity		Weight & dimensions	
USB version Ethernet LAN * Ethernet LAN (RJ-45) ports Wi-Fi * PC Audio in Card reader integrated Compatible memory cards	2.0 1 X MicroSD (TransFlash)	Display width Display depth Display height Display weight Packaging data Package width Package depth	1462.3 mm 68.9 mm 837.3 mm 29 kg 1605 mm 220 mm

Ports & interfaces		Packaging data	
PC Audio out	✓	Package height	965 mm
Audio		Package weight	37.4 kg
Built-in speaker(s) *	✓	Packaging content	
Number of built-in speakers 2	2	Remote control included	✓
RMS rated power	20 W	Cables included	HDMI
Design		Operational conditions	
Product design * Placement supported * Orientation Product colour *	nent supported * Indoor ation Horizontal It colour * Black I shape Flat mounting *	Operating temperature (T-T) Operating relative humidity (H-H) Storage temperature (T-T) Storage relative humidity (H-H)	0 - 40 °C 10 - 80% -20 - 60 °C 10 - 80%
Screen shape		Technical details	
VESA mounting * Panel mounting interface		Security updates end date	01/09/2024

