



Dahua Technology WizSense IPC-HFW2549TL-S-PV Bala (forma) Cámara de seguridad IP Interior y exterior 2960 x 1668 Píxeles Techo/escritorio

Marca : Dahua Technology

Familia de productos:
WizSense

Código del producto: DH-IPC-
HFW2549TL-S-PV

Nombre del producto : IPC-
HFW2549TL-S-PV

Dahua Technology WizSense IPC-HFW2549TL-S-PV. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/escritorio, Color del producto: Negro, Blanco, Factor de forma: Bala (forma). Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 111°, Ángulo de visión del objetivo, vertical: 58.5°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.7 mm (1 / 2.7"). Alcance normal de enfoque: 1.4 m, Distancia focal fija: 2.8 mm, Distancia de detección (angular): 63.8 m

| Performance | | Video | |
|------------------------------------|------------------------------------|-----------------------------------|--|
| Type * | IP security camera | Noise reduction | ✓ |
| Placement supported * | Indoor & outdoor | Noise reduction technology | 3D noise reduction |
| Connectivity technology * | Wired | Gain control type | Auto/Manual |
| Day/night mode | ✓ | Image quality adjustment | Mirror |
| Built-in light | ✓ | Privacy masking | ✓ |
| Dynamic range | 120 dB | Bit rate control | Constant Bit Rate (CBR)/Variable Bit Rate (VBR) |
| Design | | Bit rate | H.264: 32 kbps-8192 kbps; H.265: 12 kbps-8192 kbps |
| Form factor * | Bullet | Back Light Compensation (BLC) | ✓ |
| Mounting type * | Ceiling/Desktop | Highlight Compensation (HLC) | ✓ |
| Product colour * | Black, White | Region of Interest (ROI) encoding | ✓ |
| International Protection (IP) code | IP67 | Smart IR | ✓ |
| Camera | | Audio | |
| Minimum illumination | 0 lx | Built-in speaker(s) | ✓ |
| Angle of rotation | 360° | Built-in microphone | ✓ |
| Lens viewing angle, horizontal | 111° | Network | |
| Lens viewing angle, vertical | 58.5° | Ethernet LAN * | ✓ |
| Lens viewing angle, diagonal | 132° | Ethernet interface type | Fast Ethernet |
| Tilt angle range | 0 - 90° | Wi-Fi * | ✗ |
| Pan range | 0 - 360° | Bluetooth * | ✗ |
| White balance | Auto, Manual, Street lamp, Natural | Number of users | 20 user(s) |
| Camera shutter type | Electronic | Live view | ✓ |
| Camera shutter speed | 1/3 - 1/100000 s | Storage | |
| Adjustment shutter speed | Auto/Manual | Built-in HDD * | ✗ |
| Image sensor | | Ports & interfaces | |
| Number of sensors | 1 | Ethernet LAN (RJ-45) ports | 1 |
| Optical sensor size | 25.4 / 2.7 mm (1 / 2.7") | Security | |
| Progressive scan | ✓ | Video motion detection | ✓ |
| Sensor type * | CMOS | Mirror | ✓ |
| Lens system | | Management features | |
| Fixed focus | ✓ | Web browser | ✓ |
| Maximum aperture number | 1 | Power | |
| Normal focusing range | 1.4 m | Power source type * | DC, PoE |
| Fixed focal length | 2.8 mm | Power consumption (typical) | 2.1 W |
| Detect distance (wide) | 63.8 m | Power consumption (max) | 11.6 W |
| Detect distance (tele) | 77.8 m | | |
| Observe distance (wide) | 25.5 m | | |
| Observe distance (tele) | 31.1 m | | |
| Recognize distance (wide) | 12.8 m | | |

| Lens system | | Power | |
|---------------------------|--|---|-------------|
| Recognize distance (tele) | 15.6 m | Power consumption (Power over Ethernet (PoE)) | 2.8 W |
| Identify distance (wide) | 6.4 m | DC output voltage | 12 |
| Identify distance (tele) | 7.8 m | | |
| Night vision | | Operational conditions | |
| Night vision * | ✓ | Operating temperature (T-T) | -40 - 60 °C |
| Night vision distance | 30 m | Storage temperature (T-T) | -40 - 60 °C |
| LED type | IR/White | Operating relative humidity (H-H) | 0 - 95% |
| Video | | Weight & dimensions | |
| Maximum resolution * | 2960 x 1668 pixels | Width | 197.9 mm |
| Total megapixels * | 5 MP | Depth | 80.2 mm |
| Video compression formats | H.264, H.264+, H.264B, H.264H, H.265, H.265+, M-JPEG | Height | 76.2 mm |
| Frame rate | 30 fps | Weight | 540 g |
| Video streaming | ✓ | | |
| | | Packaging data | |
| | | Package weight | 680 g |
| | | Packaging content | |
| | | Number of cameras * | 1 |

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 26-FEB-2025. Prints or copies of Information are only valid on the printed Publication date