



## Dahua Technology WizSense IPC-HDW2249T-S-PV Domo Cámara de seguridad IP 1920 x 1080 Pixeles Techo/pared/Tubo

**Marca :** Dahua Technology

**Familia de productos:** WizSense

**Código del producto:** DH-IPC-HDW2249T-S-PV

**Nombre del producto :** IPC-HDW2249T-S-PV

Dahua Technology WizSense IPC-HDW2249T-S-PV. Tipo: Cámara de seguridad IP, Tecnología de conectividad: Alámbrico, Rango dinámico: 120 Db. Tipo de montaje: Techo/pared/Tubo, Color del producto: Blanco, Factor de forma: Domo. Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 106.1°, Ángulo de visión del objetivo, vertical: 56.4°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.8 mm (1 / 2.8"). Distancia de detección (angular): 44 m, Distancia de detección (tele): 53.7 m, Distancia de observación (angular): 17.6 m

Performance		Video	
Type *	IP security camera	Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 800 (WXGA), 1920 x 1080 (HD 1080)
Connectivity technology *	Wired	Video streaming	✓
Wide Dynamic Range (WDR)	✓	Noise reduction	✓
Day/night mode	✓	Noise reduction technology	3D noise reduction
Built-in light	✓	Gain control type	Auto/Manual
Dynamic range	120 dB	Privacy masking	✓
Certification	CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU	Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)
Design		Back Light Compensation (BLC)	✓
Form factor *	Dome	Highlight Compensation (HLC)	✓
Mounting type *	Ceiling/Wall/Pole	Region of Interest (ROI) encoding	✓
Product colour *	White	Audio	
Housing material	Metal, Plastic	Audio formats supported	G.711 A-law, G.711 µ-law, G.726, PCM
Protection features	Dust resistant	Signal-to-Noise Ratio (SNR)	56 dB
International Protection (IP) code	IP67	Network	
Camera		Ethernet LAN *	✓
Minimum illumination	0 lx	Ethernet interface type	Fast Ethernet
Angle of rotation	360°	Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP; NFS; P2P; auto registration
Lens viewing angle, horizontal	106.1°	Number of users	6 user(s)
Lens viewing angle, vertical	56.4°	Streaming method	Multicast
Lens viewing angle, diagonal	128.5°	Storage	
Tilt angle range	0 - 78°	ROM capacity	128 MB
Pan range	0 - 360°	Ports & interfaces	
White balance	Auto, Manual, Natural, Outdoor, Regional custom, Street lamp	Ethernet LAN (RJ-45) ports	1
Camera shutter type	Electronic	Security	
Camera shutter speed	1/3 -1/100000	Video motion detection	✓
Image sensor		Active tampering alarm	✓
Number of sensors	1	Intelligent Video Surveillance (IVS) system features	Intrusion, Tripwire
Optical sensor size	25.4 / 2.8 mm (1 / 2.8")	Mirror	✓
Progressive scan	✓	Management features	
Sensor type *	CMOS	Web browser	✓
Lens system			
Minimum aperture number	1		
Detect distance (wide)	44 m		
Detect distance (tele)	53.7 m		
Observe distance (wide)	17.6 m		
Observe distance (tele)	21.5 m		
Recognize distance (wide)	8.8 m		

<b>Lens system</b>		<b>Management features</b>	
Recognize distance (tele)	10.7 m	Management software	Smart PSS Lite; DSS; DMSS
Identify distance (wide)	4.4 m	<b>Power</b>	
Identify distance (tele)	5.4 m	Power source type *	DC, PoC
<b>Night vision</b>		Power consumption (typical)	1.8 W
Night vision *	✓	DC output voltage	12
Night vision distance	30 m	<b>Operational conditions</b>	
LED type	IR/White	Operating temperature (T-T)	-40 - 60 °C
Number of illumination LEDs	2	Storage temperature (T-T)	-40 - 60 °C
<b>Video</b>		Operating relative humidity (H-H)	0 - 95%
Maximum resolution *	1920 x 1080 pixels	<b>System requirements</b>	
Total megapixels *	2 MP	Mobile operating systems supported	Android, iOS
Video compression formats	H.264, H.264B, H.264H, H.265, M-JPEG	<b>Weight &amp; dimensions</b>	
		Width	103.5 mm
		Diameter	11 cm
		Weight	390 g
		<b>Packaging data</b>	
		Package weight	570 g
		<b>Packaging content</b>	
		Number of cameras *	1

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 25-FEB-2025. Prints or copies of Information are only valid on the printed Publication date