

Lenovo ThinkPad L16 Intel Core Ultra 5 125U Computadora portátil 40.6 cm (16") WUXGA 16 GB DDR5-SDRAM 512 GB SSD Wi-Fi 6E (802.11ax) Windows 11 Pro Español Negro

Marca : Lenovo

Familia de productos: ThinkPad Código del producto: 21L4000MLM

Nombre del producto : L16

- Windows 11 Pro 64-bit

- Intel Core Ultra 5 125U (12MB Cache)

- 40.6 cm (16") WUXGA 1920 x 1200 IPS

- 16GB (5600MHz) DDR5-SDRAM (1 x 16) & 512GB SSD

Intel Core Ultra 5 125U (12MB Cache), 16GB DDR5-SDRAM, 512GB SSD, 40.6 cm (16") WUXGA 1920 x 1200 IPS, Intel Graphics, LAN, WLAN, Webcam, Windows 11 Pro 64-bit

Lenovo ThinkPad L16. Tipo de producto: Computadora portátil, Factor de forma: Concha. Familia de procesador: Intel Core Ultra 5, Modelo del procesador: 125U. Diagonal de la pantalla: 40.6 cm (16"), Tipo HD: WUXGA, Resolución de la pantalla: 1920 x 1200 Pixeles. Memoria interna: 16 GB, Tipo de memoria interna: DDR5-SDRAM. Capacidad total de almacenaje: 512 GB, Unidad de almacenamiento: SSD. Modelo de gráficos en tarjeta: Intel Graphics. Sistema operativo instalado: Windows 11 Pro. Color del producto: Negro. Peso: 1.77 kg





Design		Camera	
Product type * Product colour * Form factor * Housing material	Laptop Black Clamshell Polycarbonate (PC), Acrylonitrile butadiene styrene (ABS)	Front camera resolution (numeric) Infrared (IR) camera Privacy camera Privacy type Network	5 MP ✓ ✓ Privacy shutter
Display diagonal * Display resolution * Touchscreen * HD type Panel type LED backlight Native aspect ratio Anti-glare screen Display brightness RGB colour space Colour gamut Maximum refresh rate	40.6 cm (16") 1920 x 1200 pixels X WUXGA IPS ✓ 16:10 ✓ 300 cd/m ² NTSC 45% 60 Hz	Top Wi-Fi standard * Wi-Fi standards Mobile network connection * Antenna type WLAN controller model WLAN controller manufacturer Ethernet LAN Ethernet LAN Ethernet LAN data rates Bluetooth Bluetooth version Near Field Communication (NFC) WWAN	Wi-Fi 6E (802.11ax) Wi-Fi 6E (802.11ax) × 2x2 Intel Wi-Fi 6E AX211 Intel ✓ 100,1000 Mbit/s ✓ 5.3 × Not installed
Contrast ratio (typical)	1000:1	Ports & interfaces	
Processor Processor manufacturer * Processor family * Processor generation Processor model * Processor cores Processor threads Processor boost frequency Performance cores	Intel Intel Core Ultra 5 Intel® Core™ Ultra (Series 1) 125U 12 14 4.3 GHz 2	USB 2.0 ports quantity * USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity * USB 3.2 Gen 2x2 Type-C ports quantity Ethernet LAN (RJ-45) ports HDMI ports quantity * HDMI version Thunderbolt 4 ports quantity Intel® Thunderbolt 4	1 2 1 1 2.1 1 ✓

Processor		Ports & interfaces	
Efficient cores	8	Combo headphone/mic port	1
Low Power Efficient-cores	2	USB Type-C DisplayPort Alternate	
Performance-core Max Turbo	4.3 GHz	Mode	
Frequency		USB Sleep-and-Charge	1
Efficient-core Max Turbo Frequency Low Power Efficient-core Max Turbo Frequency	3.6 GHz	USB Sleep-and-Charge ports	1
	2.1 GHz	Performance	
Performance-core base frequency	1.3 GHz	Motherboard chipset	Intel SoC
Efficient-core base frequency	0.8 GHz	Keyboard	
Low Power Efficient-core Base Frequency	700 MHz	Pointing device	ThinkPad UltraNav
Processor cache	12 MB	Numeric keypad *	1
Processor cache type	Smart Cache	Keyboard backlit	1
Processor base power	15 W	Spill-resistant keyboard	1
Maximum turbo power	57 W	Keyboard language	Spanish
Neural processor unit (NPU)		Copilot key	1
Neural processor unit (NPU)	Intel Al Boost	Software	
Maximum frequency NPU	1.4 GHz	Operating system architecture	64-bit
Sparsity support		Operating system language	Spanish
Windows Studio effects support		Operating system installed *	Windows 11 Pro
AI datatype support on NPU AI software frameworks supported	FP16, FP32, Int8 DirectML, ONNX RT, OpenVINO,	Microsoft Copilot	1
by NPU	Windows ML	Copilot+ PC	1
Memory		Battery	
Internal memory *	16 GB	Battery technology	Lithium Polymer (LiPo)
Internal memory type	DDR5-SDRAM	Number of battery cells	3
Memory clock speed	5600 MHz	Battery capacity *	57 Wh
Memory form factor	SO-DIMM	Fast charging	•
Memory layout (slots x size) Memory slots	1 x 16 GB 2x SO-DIMM	Power	
Maximum internal memory *	64 GB	AC adapter power	65 W
Memory channels	Single-channel	AC adapter frequency AC adapter input voltage	50/60 Hz 100 - 240 V
Storage	-	USB Type-C charging port *	100 - 240 V
Total storage capacity *	512 GB	USB Power Delivery (USB PD)	·
Storage media *	SSD	Security	
Total SSDs capacity	512 GB		
Number of SSDs installed	1	Cable lock slot	Konsington
SSD capacity	512 GB	Cable lock slot type Fingerprint reader	Kensington
SSD memory type SSD interface	TLC PCI Express 4.0	Smart card reader	×
NVMe	PCI Express 4.0	Jillait Calu leauei	▲
NVI-IC		Windows Hello	4
SSD form factor	✓ M.2	Windows Hello Trusted Platform Module (TPM)	4 4
SSD form factor M.2 SSD size	✓ M.2 2280 (22 x 80 mm)	Trusted Platform Module (TPM)	1
	M.2		-
M.2 SSD size	M.2 2280 (22 x 80 mm)	Trusted Platform Module (TPM) Trusted Platform Module (TPM)	1
M.2 SSD size Optical drive type * Card reader integrated	M.2 2280 (22 x 80 mm) ×	Trusted Platform Module (TPM) Trusted Platform Module (TPM) version	2.0
M.2 SSD size Optical drive type * Card reader integrated Graphics	M.2 2280 (22 x 80 mm) ×	Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection	✓ 2.0 ✓
M.2 SSD size Optical drive type * Card reader integrated	M.2 2280 (22 x 80 mm) X X	Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type	✓ 2.0 ✓
M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model *	M.2 2280 (22 x 80 mm) × × Not available	Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T)	✓ 2.0 ✓ BIOS, Power on, Supervisor 5 - 35 °C 5 - 43 °C
M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card *	M.2 2280 (22 x 80 mm) × × Not available ✓	Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	✓ 2.0 ✓ BIOS, Power on, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95%
M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer	M.2 2280 (22 x 80 mm) × × × Not available ✓ Intel	Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	 ✓ 2.0 ✓ BIOS, Power on, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95% 5 - 95%
M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card *	M.2 2280 (22 x 80 mm) × × Not available ✓ Intel ×	Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude	✓ 2.0 ✓ BIOS, Power on, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95%
 M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card * On-board graphics card family 	M.2 2280 (22 x 80 mm) × × Not available ✓ Intel × Intel Graphics	Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude Certificates	 ✓ 2.0 ✓ BIOS, Power on, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95% 5 - 95% 3048 m
M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card family On-board graphics card family On-board graphics card model *	M.2 2280 (22 x 80 mm) × × Not available ✓ Intel Intel Graphics Intel Graphics Intel Graphics	Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude Certificates Certification	 ✓ 2.0 ✓ BIOS, Power on, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95% 5 - 95%
M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card * On-board graphics card family On-board graphics card family On-board graphics card family On-board graphics card family Number of built-in speakers	M.2 2280 (22 x 80 mm) × × × Not available ✓ Intel Intel Graphics Intel Graphics Intel Graphics 2	Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude Certificates	 ✓ 2.0 ✓ BIOS, Power on, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95% 5 - 95% 3048 m ErP Lot 6 ErP Lot 26 MIL-STD-810H
M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card family On-board graphics card family On-board graphics card family On-board graphics card family On-board graphics card family Muber of built-in speakers Speaker power	M.2 2280 (22 x 80 mm) × × × Not available ✓ Intel × Intel Graphics Intel Graphics Intel Graphics 2 UN	Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude Certificates Certification	 ✓ 2.0 ✓ BIOS, Power on, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95% 5 - 95% 3048 m
M.2 SSD size Optical drive type * Card reader integrated Graphics Discrete graphics card model * On-board graphics card * On-board GPU manufacturer Discrete graphics card * On-board graphics card family On-board graphics card family On-board graphics card model *	M.2 2280 (22 x 80 mm) × × × Not available ✓ Intel Intel Graphics Intel Graphics Intel Graphics 2	Trusted Platform Module (TPM) Trusted Platform Module (TPM) version Password protection Password protection type Operational conditions Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Maximum shipping altitude Certificates Certification Sustainability	 ✓ 2.0 ✓ BIOS, Power on, Supervisor 5 - 35 °C 5 - 43 °C 8 - 95% 5 - 95% 3048 m ErP Lot 6 ErP Lot 26 MIL-STD-810H ENERGY STAR, EPEAT Gold, ErP,

Camera		Weight & dimensions	
Front camera	•	Width Depth Height Weight *	357.2 mm 253.4 mm 20.8 mm 1.77 kg
		Packaging content	
		AC adapter included *	✓





198153952106

0198153952106

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.