




## TP-Link EAP215-Bridge KIT 867 Mbit/s Blanco Energía sobre Ethernet (PoE)

**Marca :** TP-Link

**Código del producto:** EAP215-BRIDGE KIT

**Nombre del producto :** EAP215-Bridge KIT

TP-Link EAP215-Bridge KIT. 5 GHz, Rango máximo de transferencia de datos: 867 Mbit/s. Algoritmos de seguridad: SNMP, SNMPv2, SNMPv3, SSH. Ethernet LAN, velocidad de transferencia de datos: 10,100,1000 Mbit/s. Energía sobre Ethernet (PoE). Color del producto: Blanco



Features		Power	
2.4 GHz *	✗	Power over Ethernet (PoE) *	✓
5 GHz *	✓	Power over Ethernet (PoE) type supported	Passive PoE
6 GHz *	✗	DC voltage range	12 V
Maximum data transfer rate *	867 Mbit/s	Design	
Maximum data transfer rate (5 GHz)	867 Mbit/s	Placement *	Pole
Ethernet LAN data rates	10,100,1000 Mbit/s	Product colour *	White
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11be, IEEE 802.11g, IEEE 802.11n	Reset button	✓
Cabling technology	10/100/1000Base-T(X)	LED indicators	✓
MIMO	✓	Antenna	
MIMO type	Multi User MIMO	Antenna type *	Internal
VLAN support	✓	Antenna direction type	Directional
Rate limiting	✓	Antenna features	Integrated antenna
Quality of Service (QoS) support	✓	Antenna gain level (max)	11 dBi
BeamForming	✓	Polarization	Dual polarization
Transmitting power (CE)	<23dBm (5 GHz, band 1/2, EIRP); <30dBm (5 GHz band3, EIRP)	Certificates	
Transmitting power (FCC)	<22dBm (5 GHz band1/4)	Certification	CE, FCC, RoHS
Security		Weight & dimensions	
Security algorithms *	SNMP, SNMPv2, SNMPv3, SSH	Width	224 mm
MAC address filtering	✓	Depth	79 mm
Remote Authentication Dial-In User Service (RADIUS)	✓	Height	60 mm
Access Control List (ACL)	✓	Weight	330.9 g
Management features		Packaging content	
Web-based management	✓	Quick start guide	✓
		Operational conditions	
		Operating relative humidity (H-H)	10 - 90%

Management features		Operational conditions	
Syslog	✓	Operating temperature (T-T)	-40 - 70 °C
Ports & interfaces		Storage temperature (T-T)	-40 - 70 °C
Ethernet LAN (RJ-45) ports *	3	Storage relative humidity (H-H)	5 - 90%



4895252502565



0840030709159



840030709159



4895252502572



8885020627077



8885020627084



0810142823388



810142823388

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.