

## LG 49VL5PJ pantalla de señalización Pantalla plana de señalización digital 124.5 cm (49") IPS 500 cd / m² Full HD Negro WebOS 24/7

Marca: LG Código del producto: 49VL5PJ

Nombre del producto: 49VL5PJ

LG 49VL5PJ. Diseño de producto: Pantalla plana de señalización digital. Diagonal de la pantalla: 124.5 cm (49"), Tecnología de visualización: IPS, Resolución de la pantalla: 1920 x 1080 Pixeles, Brillo de pantalla: 500 cd / m², Tipo HD: Full HD. Horas de funcionamiento (horas/días): 24/7. Sistema operativo instalado: WebOS. Color del producto: Negro





Display		Performance	
Panel type	LCD	Number of OSD languages	21
Direct-LED Display diagonal * 124.5 cm (49") Display technology * IPS Display resolution * 1920 x 1080 pixels Display brightness * 500 cd/m²	On Screen Display (OSD) languages	Arabic, Simplified Chinese, Traditional Chinese, Czech, Danish, German, Dutch, English, Spanish, Finnish, French, Greek, Italian, Japanese, Korean, Norwegian, Portuguese, Russian, Swedish, Turkish	
HD type *	Full HD	Operating hours (hours/days)	24/7
Touchscreen *	X	HDCP	✓
Native aspect ratio	16:9	International Protection (IP) code	IP5X
Response time Contrast ratio (typical)	8 ms 1000:1	HDCP version	2.2
Contrast ratio (dynamic)	500000:1	Power	
Viewing angle, horizontal	178°	Power consumption (typical) *	110 W
Viewing angle, vertical	178°	Power consumption (standby) *	0.5 W
Display number of colours	1.07 billion colours	Power consumption (off)	0.5 W
Display diagonal (metric)	123.2 cm	Energy efficiency class (SDR)	G
Rated lifetime	60000 h	Energy consumption (SDR) per 1000 hours	73.2 kWh
Native refresh rate	60 Hz	AC input voltage	100 - 240 V
Haze rate	3%	AC input frequency	50 - 60 Hz
Ports & interfaces		Heat dissipation	375 BTU/h
HDMI ports quantity *	2	Energy efficiency scale	A to G
HDMI version	2.2	Computer system	
DVI port * DisplayPorts quantity *	<b>✓</b> 1	Operating system installed	WebOS
USB port *	✓	Weight & dimensions	
USB ports quantity	1	Display width	1077.6 mm
USB version	2.0	Display depth	89.7 mm
Ethernet LAN *	✓	Display height	607.8 mm
Ethernet LAN (RJ-45) ports	1	Display weight	17.8 kg
Audio (L/R) in	1	Packaging data	
Audio (L/R) out	1	Package width	1198 mm
RS-232 interface	✓	Package depth	756 mm
Remote (IR) input	1	Package height	247 mm
		Package weight	21.9 kg

Design		Packaging content	
Product design *	Digital signage flat panel	Remote control included	✓
Placement supported *	Indoor	Batteries included	✓
Orientation Product colour *	Horizontal Black	Cables included	AC, DisplayPort, IR sensor, LAN (RJ-45), RS-232
VESA mounting *	✓	Mounting kit	✓
Panel mounting interface	600 x 400 mm 1.25 mm 2.25 mm 2.25 mm	Operational conditions	
Bezel width (bottom)  Bezel width (side)  Bezel width (top)		Operating temperature (T-T) Operating relative humidity (H-H)	0 - 40 °C 10 - 80%
Performance		Features	
Purpose *	Universal	Heat dissipation (max)	409 BTU/h
Browsing	✓	Technical details	
On Screen Display (OSD)	•	Internal memory Sustainability certificates	8 MB ENERGY STAR
		Compliance certificates	CE

