

Samsung LH50QHCEBGC Pantalla plana de señalización digital 127 cm (50") Wifi 700 cd / m² 4K Ultra HD Negro Procesador incorporado Tizen 24/7

Marca : Samsung

Código del producto: LH50QHCEBGCXGO

Nombre del producto : LH50QHCEBGC

Samsung LH50QHCEBGC. Diseño de producto: Pantalla plana de señalización digital. Diagonal de la pantalla: 127 cm (50"), Resolución de la pantalla: 3840 x 2160 Píxeles, Brillo de pantalla: 700 cd / m², Tipo HD: 4K Ultra HD. Wifi. Horas de funcionamiento (horas/días): 24/7. Sistema operativo instalado: Tizen. Color del producto: Negro



Display		Design	
Panel type	VA	Screen shape	Flat
Display diagonal *	127 cm (50")	VESA mounting *	✓
Display resolution *	3840 x 2160 pixels	Panel mounting interface	200 x 200 mm
Display brightness *	700 cd/m²	Bezel width (bottom)	1.15 cm
HD type *	4K Ultra HD	Bezel width (side)	1.15 cm
Touchscreen *	✗	Bezel width (top)	1.15 cm
Response time	10 ms	Anti-glare screen	✓
Contrast ratio (typical)	4000:1	Mounting type	Wall
Dynamic contrast ratio marketing name	Mega Contrast	Performance	
Viewing angle, horizontal	178°	Purpose *	Universal
Viewing angle, vertical	178°	Operating hours (hours/days)	24/7
Pixel pitch	0.285 x 0.285 mm	HDCP	✓
Display diagonal (metric)	127 cm	HDCP version	2.2
Number of displays	1	Power	
Horizontal scan range	30 - 81 kHz	Power consumption (typical) *	165 W
Vertical scan range	48 - 75 Hz	Power consumption (sleep)	0.5 W
RGB colour space	NTSC	AC input voltage	100 - 240 V
Ports & interfaces		AC input frequency	50/60 Hz
HDMI ports quantity *	3	Computer system	
HDMI version	2.0	Computer system *	✓
HDMI input ports quantity	3	Built-in processor *	✓
DVI port *	✗	Internal storage capacity	16 GB
DisplayPorts quantity *	1	Operating system installed	Tizen
DisplayPorts in	1	Operating system version	7.0
USB port *	✓	Weight & dimensions	
USB ports quantity	2	Display width	1124.1 mm
Ethernet LAN *	✓	Display depth	28.5 mm
Ethernet LAN (RJ-45) ports	1	Display height	644.8 mm
Wi-Fi *	✓	Display weight	12.4 kg
RS-232 interface	✓	Packaging data	
Infrared data port	✓	Package width	1246 mm
Remote (IR) input	1	Package depth	131 mm
		Package height	761 mm

Design		Packaging data	
Product design *	Digital signage flat panel	Package weight	16.2 kg
Placement supported *	Indoor	Operational conditions	
Product colour *	Black	Operating temperature (T-T)	0 - 40 °C
		Operating relative humidity (H-H)	10 - 80%

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date