

Dahua Technology Entry IPC-HFW1830S-S6 cámara de vigilancia Bala (forma) Cámara de seguridad IP Interior y exterior 3840 x 2160 Pixeles Techo/pared

Marca : Dahua Technology Familia de productos: Entry Código del producto: IPC-HFW1830S-S6

Nombre del producto: IPC-

HFW1830S-S6

Dahua Technology Entry IPC-HFW1830S-S6. Tipo: Cámara de seguridad IP, Colocación compatible: Interior y exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared, Color del producto: Negro, Blanco, Factor de forma: Bala (forma). Iluminación mínima: 0.04 Lux, Ángulo de rotación: 360°, Ángulo de visión del objetivo, horizontal: 105°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 2.7 mm (1 / 2.7"). Distancia focal fija: 2.8 mm, Distancia más cercana de enfoque: 10 m

Performance		Video	
	ID as a with a second of		
Type * Placement supported * Connectivity technology * Wide Dynamic Range (WDR) Day/night mode Certification	IP security camera Indoor & outdoor Wired CE-LVD: EN62368-1 CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B	Noise reduction Noise reduction technology Gain control type Privacy masking Bit rate control Bit rate	→ 3D noise reduction Auto/Manual → Constant Bit Rate (CBR), Variable Bit Rate (VBR) H.264: 32 kbps-8192 kbps H.265: 12 kbps-8192 kbps
Design		Back Light Compensation (BLC) Highlight Compensation (HLC)	<i>1</i>
Form factor *	Bullet	Region of Interest (ROI) encoding	v
Mounting type *	Ceiling/wall	Audio	
Product colour * Housing material International Protection (IP) code	Black, White Metal IP67	Audio formats supported Signal-to-Noise Ratio (SNR) Built-in microphone	G.711 A-law, G.726, PCM 56 dB
Camera		·	•
Minimum illumination Angle of rotation	0.04 lx 360°	Network Ethernet LAN *	✓
Lens viewing angle, horizontal Lens viewing angle, vertical	105° 56°	Supported network protocols	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; SMTP; FTP; DHCP; DNS; DDNS; NTP; Multicast
Lens viewing angle, diagonal Tilt angle range	125° 0 - 90°	Wi-Fi *	x
Pan range	0 - 360°	Bluetooth *	×
White balance	Auto, Manual, Natural, Outdoor, Street lamp	Storage	
Camera shutter type Camera shutter speed Adjustment shutter speed	Electronic 1/3 s-1/100000 Auto/Manual	Built-in HDD * Internal memory ROM capacity	X 256 MB 16 MB
Image sensor		Ports & interfaces	
Optical sensor size	25.4 / 2.7 mm (1 / 2.7")	Ethernet LAN (RJ-45) ports	1
Progressive scan	✓	Security	
Sensor type *	CMOS	Video motion detection	✓
Panoramic camera		Management features	
Digital Wide Dynamic Range (DWDR) (panoramic camera)	✓	Management software	Smart PSS; DSS; DMSS
Lens system		Power	
Number of lenses * Maximum aperture number Fixed focal length	1 2 2.8 mm	Power source type * Power consumption (typical) Power consumption (Power over Ethernet (PoE))	DC, PoC 4.4 W 5.2 W
Closest focusing distance	10 m	DC output voltage	12

Night vision		Operational conditions	
Night vision * Night vision distance LED type	√ 30 m IR	Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H)	-40 - 60 °C -40 - 60 °C 0 - 95%
Number of illumination LEDs	1	System requirements	
Video		Mobile operating systems supported	d Android, iOS
Maximum resolution *	3840 x 2160 pixels	Weight & dimensions	
Total megapixels *	8 MP	Height	162.1 mm
Video compression formats	H.264, H.264+, H.264B, H.265, H.265+, M-IPEG	Diameter	7.01 cm
Supported graphics resolutions	352 x 240, 352 x 288, 640 x 480 (VGA), 704 x 480, 704 x 576, 1280 x 720 (HD 720), 1280 x 960, 1920 x 1080 (HD 1080), 2048 x 1536 (QXGA), 2304 x 1296, 2592 x 1944, 2688 x 1520, 3072 x 1728, 3072 x 2048, 3840 x 2160	Weight	320 g
		Packaging data	
		Package weight	450 g
		Packaging content	
		Number of cameras *	1
Frame rate	30 fps		

