Verbatim 32157 nodo concentrador USB 3.2 Gen 1 (3.1 Gen 1) Type-C 5000 Mbit/s Gris

Marca : Verbatim

Código del producto: 32157

Nombre del producto : 32157

Verbatim 32157. Interfaz de host: USB 3.2 Gen 1 (3.1 Gen 1) Type-C, Interfaces de concentradores: HDMI, RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 1 (3.1 Gen 1) Type-C. Velocidad de transferencia de datos: 5000 Mbit/s, Formatos gráficos soportados: 3840 x 2160, Resolución máxima (HDMI): 3840 x 2160 Pixeles. Tipo de interfaz ethernet: Gigabit Ethernet, Ethernet LAN, velocidad de transferencia de datos: 100,1000 Mbit/s. Tipo de fuente de alimentación: USB, Voltaje de entrada: 5 - 20 V, Voltaje de salida: 5 V. Sistemas operativos Windows soportados: Windows 10, Windows 11, Windows 7, Windows 8, Sistemas operativos Mac soportados: Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High..., Otros sistemas operativos soportados: Android






Ports & interfaces

Host interface *	USB 3.2 Gen 1 (3.1 Gen 1) Type-C	Other operating systems supported	Android
Hub interfaces *	HDMI, RJ-45, USB 3.2 Gen 1 (3.1 Gen 1) Type-A, USB 3.2 Gen 1 (3.1	Weight & dimensions	
USB 3.2 Gen 1 (3.1 Gen 1) Type-A	Gen 1) Type-C	Width Depth	47 mm 105 mm
ports quantity	3	Height	16.4 mm
USB 3.2 Gen 1 (3.1 Gen 1) Type-C ports quantity	1	Weight	80 g
HDMI ports quantity	1	Packaging data	
Ports quantity *	6	Quantity per pack	1 pc(s)
Ethernet LAN (RJ-45) ports	1	Package width	85 mm
Features		Package depth	155 mm
Data transfer rate *	5000 Mbit/s	Package height	22 mm
Supported graphics resolutions	3840 x 2160	Package weight	130 g
Maximum resolution (HDMI)	3840 x 2160 pixels	Package type	Box
Product colour	Grey	Packaging content	
Housing material	Acrylonitrile butadiene styrene (ABS), Aluminium	Quick start guide	1
USB Power Delivery (USB PD)	1	Operational conditions	
USB Power Delivery revision	3.0	Minimum operating temperature	0 °C
USB Power Delivery up to	100 W	Maximum operating temperature	40 °C
			0 40.00
HD type	4K Ultra HD	Operating temperature (T-T)	0 - 40 °C
	4K Ultra HD 1	Storage temperature (T-T)	-20 - 70 °C
HD type			
HD type Number of displays supported	1	Storage temperature (T-T)	-20 - 70 °C
HD type Number of displays supported Cable type	1 Round cable	Storage temperature (T-T) Operating relative humidity (H-H)	-20 - 70 °C
HD type Number of displays supported Cable type Cable length	1 Round cable 0.15 m	Storage temperature (T-T) Operating relative humidity (H-H) Logistics data	-20 - 70 °C 10 - 85%
HD type Number of displays supported Cable type Cable length Plug and Play	1 Round cable 0.15 m	Storage temperature (T-T) Operating relative humidity (H-H) Logistics data Pallet gross width	-20 - 70 °C 10 - 85% 100 cm
HD type Number of displays supported Cable type Cable length Plug and Play Country of origin Network	1 Round cable 0.15 m ✓ China	Storage temperature (T-T) Operating relative humidity (H-H) Logistics data Pallet gross width Pallet gross length Pallet gross height Pallet gross weight	-20 - 70 °C 10 - 85% 100 cm 120 cm 120 cm 310 kg
HD type Number of displays supported Cable type Cable length Plug and Play Country of origin	1 Round cable 0.15 m	Storage temperature (T-T) Operating relative humidity (H-H) Logistics data Pallet gross width Pallet gross length Pallet gross height Pallet gross weight Master (outer) case width	-20 - 70 °C 10 - 85% 100 cm 120 cm 120 cm 310 kg 256 mm
HD type Number of displays supported Cable type Cable length Plug and Play Country of origin Network Ethernet interface type Ethernet LAN data rates	1 Round cable 0.15 m ✓ China Gigabit Ethernet	Storage temperature (T-T) Operating relative humidity (H-H) Logistics data Pallet gross width Pallet gross length Pallet gross height Pallet gross weight Master (outer) case width Master (outer) case length	-20 - 70 °C 10 - 85% 100 cm 120 cm 120 cm 310 kg 256 mm 345 mm
HD type Number of displays supported Cable type Cable length Plug and Play Country of origin Network Ethernet interface type	1 Round cable 0.15 m ✓ China Gigabit Ethernet	Storage temperature (T-T) Operating relative humidity (H-H) Logistics data Pallet gross width Pallet gross length Pallet gross height Pallet gross weight Master (outer) case width	-20 - 70 °C 10 - 85% 100 cm 120 cm 120 cm 310 kg 256 mm

System requirements

Power		Technical details	
Output voltage Output current	5 V 0.9 A	Pallet net height Pallet net length	12 cm 120 cm
System requirements		Pallet net width	100 cm
Windows operating systems supported	Windows 10, Windows 11, Windows 7, Windows 8	Pallet net weight	12 kg CE, Electromagnetic Compatibility (EMC), Federal Communications
Mac operating systems supported	Mac OS X 10.10 Yosemite, Mac OS X 10.11 El Capitan, Mac OS X 10.12 Sierra, Mac OS X 10.13 High Sierra, Mac OS X 10.14 Mojave, Mac OS X 10.15 Catalina, Mac OS X 10.15.3 Catalina, Mac OS X 10.2 Jaguar, Mac OS X 10.3 Panther, Mac OS X 10.4 Tiger, Mac OS X 10.5 Leopard, Mac OS X 10.6 Snow Leopard, Mac OS X 10.7 Lion, Mac OS X 10.7.5 Lion, Mac OS X 10.8 Mountain Lion, Mac OS X 10.9 Mavericks, Mac OS X 11.0 Big Sur, Mac OS X 12.0 Monterey, Mac OS X 13.0 Ventura, Mac OS X 14.0 Sonoma		Commission (FCC), Low Voltage Directive (LVD), REACH, RoHS, UKCA

Linux operating systems supported 🖌





023942321576

0023942321576

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.