

Verbatim Mini GaN Charger 70W Universal Negro Corriente alterna Carga rápida Interior

Marca : Verbatim

Código del producto: 32229

Nombre del producto : Mini GaN Charger 70W

Verbatim Mini GaN Charger 70W. Tipo de cargador: Interior, Tipo de alimentación: Corriente alterna, Compatibilidad del cargador: Universal. Voltaje de entrada: 100 - 240 V, Voltaje de salida máximo: 20 V. Número de puertos USB Tipo C: 2, Carga rápida, Funciones de protección de poder: Sobrecorriente, Sobrevoltaje, Sobrecalentamiento, Cortocircuito. Color del producto: Negro



Performance		Power	
Charger compatibility *	Universal	Output current (9V)	3 A
Power source type *	AC	Output current (12V)	3 A
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	Output current (15V)	3 A
USB Type-C ports quantity	2	Output current (20V)	3.5 A
Fast charging	✓	Port 1 output current	3.5 A
Fast charging technology	Quick Charge 3.0	Port 2 output current	3.5 A
Charger type *	Indoor	Port 3 output current	3 A
Number of simultaneously connected devices (max) *	3	Weight & dimensions	
Programmable power supply (PPS)	✓	Width	31 mm
USB Power Delivery (USB PD)	✓	Depth	54 mm
Operating principle	Contact	Height	54 mm
USB Power Delivery revision	3.0	Weight	120 g
USB Power Delivery up to	70 W	Packaging data	
Power protection features	Over current, Over voltage, Overheating, Short circuit	Package width	47 mm
Design		Package depth	110 mm
Product colour *	Black	Package height	123 mm
Housing material	Polycarbonate (PC)	Package weight	230 g
LED indicators	✓	Package type	Box
Plug and Play	✓	Packaging content	
Gallium nitride (GaN) transistors	✓	Quantity per pack	1 pc(s)
Power		AC adapter included	✓
Input voltage	100 - 240 V	Included power plug types	EU, UK, US
Input frequency	50/60 Hz	Logistics data	
Input current	1.8 A	Warranty period	2 year(s)
Maximum power	70 W	Master (outer) cases per pallet layer	8 pc(s)
		Layers per pallet	4 pc(s)

Power		Other features	
Maximum output voltage	20 V	Gross weight of outer carton	11520 kg
Minimum output voltage	3.3 V	Quantity inner carton	10 pc(s)
Port 1 output power	70 W	Quantity outer carton	40 pc(s)
Port 2 output power	70 W	Inner carton dimensions (W x D x H)	255 x 265 x 130 mm
Port 3 output power	30 W	Outer carton dimensions (W x D x H)	270 x 560 x 290 mm
Output current (5V)	3 A	User guide	✓



0023942322290



023942322290

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.