

## Verbatim GaN Charger 65W Universal Negro Corriente alterna Carga rápida Interior

**Marca :** Verbatim

**Código del producto:** 32217

**Nombre del producto :** GaN Charger 65W

Verbatim GaN Charger 65W. Tipo de cargador: Interior, Tipo de alimentación: Corriente alterna, Compatibilidad del cargador: Universal. Voltaje de entrada: 100 - 240 V, Voltaje de salida máximo: 20 V. Número de puertos USB Tipo C: 1, Carga rápida, Funciones de protección de poder: Sobrecorriente, Sobrevoltaje, Sobrecalentamiento, Cortocircuito. Longitud de cable: 0.8 m, Color del producto: Negro



Performance		Power	
Charger compatibility *	Universal	Output current (9V)	3 A
Power source type *	AC	Output current (12V)	3 A
USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity	1	Output current (15V)	3 A
USB Type-C ports quantity	1	Output current (20V)	3.25 A
Fast charging	✓	Port 1 output current	4.5 A
Fast charging technology	Quick Charge 3.0	Port 2 output current	3 A
Charger type *	Indoor	Weight & dimensions	
Number of simultaneously connected devices (max) *	3	Width	50 mm
Programmable power supply (PPS)	✓	Depth	58.5 mm
USB Power Delivery (USB PD)	✓	Height	50 mm
Operating principle	Contact	Weight	157 g
USB Power Delivery revision	3.0	Packaging data	
USB Power Delivery up to	65 W	Package width	53 mm
Power protection features	Over current, Over voltage, Overheating, Short circuit	Package depth	110 mm
		Package height	123 mm
		Package weight	255 g
		Package type	Box
Design		Packaging content	
Product colour *	Black	Retractable cable	✓
Cable length	0.8 m	Quantity per pack	1 pc(s)
Housing material	Polycarbonate (PC)	AC adapter included	✓
Plug and Play	✓	Included power plug types	EU, UK, US
Gallium nitride (GaN) transistors	✓	Logistics data	
Power		Master (outer) cases per pallet layer	16 pc(s)
Input voltage	100 - 240 V	Layers per pallet	4 pc(s)
Input frequency	50/60 Hz		
Input current	1.7 A		
Maximum power	65 W		

Power		Other features	
Maximum output voltage	20 V	Built-in display	✓
Minimum output voltage	5 V	Net weight inner carton	2900 kg
Port 1 output power	65 W	Net weight of outer carton	6550 kg
Port 2 output power	60 W	Inner carton dimensions (W x D x H)	265 x 285 x 130 mm
Output current (5V)	3 A	Outer carton dimensions (W x D x H)	280 x 300 x 290 mm
		User guide	✓



0023942322177



023942322177

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.