

DELL S Series S2725H LED display 68.6 cm (27") 1920 x 1080 Pixeles Full HD LCD Negro, Plata

Marca : DELL Familia de productos: S

Código del producto: DELLSeries S2725H

Nombre del producto :

S2725H

- 68.6cm (27") Full HD 1920 x 1080 Edge LED IPS
- -8ms, 16:9, 1500:1
- HDMI

68.6cm (27") Full HD 1920 x 1080 Edge LED IPS, 16:9, 16.78M, 8ms, 178°/178°, 1500:1

DELL S Series S2725H LED display 68.6 cm (27") 1920 x 1080 Pixeles Full HD LCD Negro, Plata:

Monitor FHD de 27 pulgadas que optimiza la comodidad visual y cuenta con imágenes impresionantes y una acústica excepcional en un diseño inspirado en el estilo de vida.

DELL S Series S2725H. Diagonal de la pantalla: 68.6 cm (27"), Resolución de la pantalla: 1920 x 1080 Pixeles, Tipo HD: Full HD, Tecnología de visualización: LCD, Tiempo de respuesta: 8 ms, Relación de aspecto nativa: 16:9, Ángulo de visión, horizontal: 178°, Ángulo de visión, vertical: 178°. Altavoces incorporados. montaje VESA. Color del producto: Negro, Plata





Display		Power	
Display diagonal * Display resolution * HD type *	68.6 cm (27") 1920 x 1080 pixels Full HD	Energy efficiency class (SDR) * Energy consumption (SDR) per 1000 hours *	D 17 kWh
Native aspect ratio * Display technology * Panel type * LED backlight Backlight type Touchscreen * Display brightness (typical) Response time * Anti-glare screen	ive aspect ratio * play technology * play backlight icklight type play brightness (typical)	Power consumption (typical) * Power consumption (standby) * Power consumption (max) Power consumption (off) AC input voltage AC input frequency Input current Power supply type Energy efficiency scale European Product Registry for Energy Labelling (EPREL) code	17 W 0.4 W 45 W 0.3 W 100 - 240 V 50/60 Hz 1.5 A Internal A to F
Supported video modes		Operational conditions	
Contrast ratio (typical) * Maximum refresh rate * Viewing angle, horizontal Viewing angle, vertical Display number of colours * Response time (fast)		Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Operating altitude Non-operating altitude	0 - 40 °C -20 - 60 °C 10 - 80% 5 - 90% 0 - 5000 m 5000 - 12192 m
Pixel pitch Pixel density	0.3114 x 0.3114 mm 82 ppi	Weight & dimensions	
Horizontal scan range Vertical scan range Viewable size, horizontal Viewable size, vertical Surface hardness sRGB coverage (typical)	al scan range 30 - 110 kHz scan range 48 - 100 Hz e size, horizontal 59.8 cm e size, vertical 33.6 cm hardness 3H	Width (with stand) Depth (with stand) Height (with stand) Weight (with stand) Width (without stand) Depth (without stand) Height (without stand)	609.7 mm 176.5 mm 452.2 mm 4.94 kg 609.7 mm 59 mm 354.2 mm

Performance		Weight & dimensions	
NVIDIA G-SYNC *	X	Weight (without stand)	4.3 kg
AMD FreeSync *	×	Bezel width (side)	5.9 mm
Flicker-free technology	✓	Bezel width (top)	5.89 mm
Low Blue Light technology	✓	Bezel width (bottom)	1.2 cm
Multimedia		Packaging data	
Number of speakers	2	Package weight	7.31 kg
RMS rated power	10 W	Packaging content	
Built-in speaker(s) *	✓	Stand included	✓
Built-in camera *	×	Cables included	AC, HDMI
Design		Quick start guide	✓
-	Office	HDMI cable length	1.8 m
Market positioning * Product colour *	Black, Silver	Sustainability	
Front bezel colour	Black	Sustainability compliance	✓
Feet colour	Silver	Sustainability certificates	ENERGY STAR
Ports & interfaces		Doesn't contain	PVC/BFR
Built-in USB hub *	X	Carbon footprint	
HDMI *	✓	Total carbon footprint (kg of CO2e)	188
HDMI ports quantity	2	Carbon emissions, manufacturing	84
HDMI version	1.4	(kg of CO2e)	
Headphone out *	×	Carbon emissions, logistics (kg of CO2e)	14
HDCP	✓	Carbon emissions, energy usage (kg	84
HDCP version	1.4	of CO2e)	04
AC (power) in	✓	Carbon emissions, end-of-life (kg of CO2e)	7
Ergonomics		Total carbon emissions, w/o use phase (kg of CO2e)	104
VESA mounting *	✓	PAIA version	GaBi version 1, 2024
Panel mounting interface	100 x 100 mm	Other features	
Cable lock slot *	✓		Ha (maraum)
Cable lock slot type	Kensington	Heavy metals free Compliance certificates	Hg (mercury) RoHS
Height adjustment *	×	Compliance certificates	ROTTS
Tilt adjustment	✓		
Tilt angle range	-5 - 21°		
On Screen Display (OSD)	✓		
Plug and Play	✓		
LED indicators	✓		





5397184821619

0884116465089



884116465089

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.