



LG 22SM3G-B pantalla de señalización Pantalla plana de señalización digital 54.6 cm (21.5") IPS Wifi 250 cd / m² Full HD Negro Procesador incorporado 16/7

Marca : LG

Código del producto: 22SM3G-B

Nombre del producto : 22SM3G-B

LG 22SM3G-B. Diseño de producto: Pantalla plana de señalización digital. Diagonal de la pantalla: 54.6 cm (21.5"), Tecnología de visualización: IPS, Resolución de la pantalla: 1920 x 1080 Píxeles, Brillo de pantalla: 250 cd / m², Tipo HD: Full HD. Wifi. Horas de funcionamiento (horas/días): 16/7. Color del producto: Negro



Display		Power	
Display diagonal *	54.6 cm (21.5")	Power consumption (typical) *	33 W
Display technology *	IPS	Power consumption (standby) *	30 W
Display resolution *	1920 x 1080 pixels	Power consumption (sleep)	1 W
Display brightness *	250 cd/m²	Power consumption (off)	0.5 W
HD type *	Full HD	AC input voltage	100 - 240 V
Touchscreen *	✗	AC input frequency	50 - 60 Hz
Native aspect ratio	16:9	Heat dissipation	7.89 BTU/h
Contrast ratio (typical)	1000:1	Computer system	
Contrast ratio (dynamic)	400000:1	Computer system *	✗
Viewing angle, horizontal	178°	Built-in processor *	✓
Viewing angle, vertical	178°	Processor cores	4
Display diagonal (metric)	55.88 cm	Internal memory	4 GB
Ports & interfaces		Weight & dimensions	
HDMI ports quantity *	2	Width	510.3 mm
DVI port *	✗	Depth	53.8 mm
USB port *	✓	Height	302.1 mm
USB ports quantity	1	Weight	3.34 kg
USB version	2.0	Packaging data	
Ethernet LAN *	✓	Package width	565 mm
Ethernet LAN (RJ-45) ports	1	Package depth	103 mm
Wi-Fi *	✓	Package height	357 mm
Audio (L/R) in	1	Package weight	3.5 kg
RS-232 interface	✓	Packaging content	
RS-232C	✓	Remote control included	✓
Audio		Batteries included	✓
Built-in speaker(s) *	✓	Cables included	AC
Number of built-in speakers	2	Mounting kit	✓
RMS rated power	2 W	Operational conditions	
Design		Operating temperature (T-T)	0 - 40 °C
Product design *	Digital signage flat panel	Operating relative humidity (H-H)	10 - 80%
Orientation	Horizontal	Storage temperature (T-T)	-20 - 60 °C
Product colour *	Black	Storage relative humidity (H-H)	5 - 85%
VESA mounting *	✓		

Design		Certificates	
Panel mounting interface	100 x 100 mm	Certification	CB, NRTL, EMC, FCC Class "A", CE, ErP
Performance		Logistics data	
Purpose *	Universal	Harmonized System (HS) code	85285210
Operating hours (hours/days)	16/7		



8806098661039



0719192636200



719192636200



8806098661060

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.