



APC SMC1500-2UC sistema de alimentación ininterrumpida (UPS)
Línea interactiva 1.44 kVA 900 W

Marca : APC

Código del producto: SMC1500-2UC

Nombre del producto : SMC1500-2UC



APC SMC1500-2UC. Topología UPS: Línea interactiva, Capacidad de potencia de salida (VA): 1.44 kVA, Potencia de salida: 900 W. Tecnología de batería: Plomo-ácido, Duración de la batería (máx): 6 Año(s), Tiempo de recarga de la batería: 3 h. Factor de forma: Montaje en rack o Montaje en bastidor, Color del producto: Negro, Tipo de visualizador: LCD. Certificados de cumplimiento: RoHS, Certificación: CSA C22.2 No 107.1, CULus, ENERGY STAR V2.0 (USA), FCC part 15 class A, ICES-003, UL 1778. Cables incluidos: Cable USB



Features		Design	
UPS topology *	Line-Interactive	Form factor *	Rackmount
Output power capacity *	1.44 kVA	Built-in fan	✓
Output power *	900 W	Product colour *	Black
Waveform *	Sine	Display type	LCD
Input operation voltage (min) *	93 V	Operational conditions	
Input operation voltage (max) *	130 V	Operating temperature (T-T)	0 - 40 °C
Input frequency *	50/60 Hz	Storage temperature (T-T)	-15 - 40 °C
Output operation voltage (min)	110 V	Operating relative humidity (H-H)	0 - 95%
Output operation voltage (max)	125 V	Operating altitude	0 - 3048 m
Output frequency	50/60 Hz	Non-operating altitude	0 - 15240 m
Automatic Voltage Regulation (AVR)	✓	Certificates	
Surge energy rating	680 J	Compliance certificates	RoHS
Response time	10 ms	Certification	CSA C22.2 No 107.1, CULus, ENERGY STAR V2.0 (USA), FCC part 15 class A, ICES-003, UL 1778
Noise level	45 dB		
Audible alarm(s)	✓	Packaging content	
Audible alarm modes	Alarm when on battery, Low battery alarm	Rack mount kit	✓
Ports & interfaces		Cables included	USB cable
USB port	✓	Quick installation guide	✓
Ethernet LAN (RJ-45) ports	1	Sustainability	
Battery		Sustainability certificates	ENERGY STAR
Battery technology	Lead-Acid	Weight & dimensions	
Battery life (max)	6 year(s)	Width	432 mm
Battery recharge time	3 h	Depth	477 mm
Cold start	✓	Height	86 mm
		Weight	25.3 kg

Packaging data

Package width	590 mm
Package depth	610 mm
Package height	235 mm
Package weight	29.1 kg

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-APR-2025. Prints or copies of Information are only valid on the printed Publication date