

CyberPower LX1500GU sistema de alimentación ininterrumpida (UPS) Línea interactiva 1.5 kVA 900 W 10 salidas AC

Marca : CyberPower

Código del producto: LX1500GU

Nombre del producto : LX1500GU

900 W, NEMA 5-15R x 10

CyberPower LX1500GU sistema de alimentación ininterrumpida (UPS) Línea interactiva 1.5 kVA 900 W 10 salidas AC:

CyberPower LX1500GU garantiza el respaldo de energía para dispositivos multimedia, equipos de TI, computadoras, dispositivos de almacenamiento / NAS, dispositivos de telecomunicaciones, dispositivos de red, sistemas de seguridad / emergencia y sistemas de vigilancia. El producto adopta una topología de línea interactiva con la función de Regulación Automática de Voltaje (AVR) para ofrecer una salida de potencia de CA estable. El producto también está calificado por EnergyStar con nuestra tecnología de Ahorro de Energía.

El UPS proporciona respaldo de batería, tomacorrientes y filtro EMI para proteger sus dispositivos. Cuenta con protección para línea de datos, pantalla LCD multifunción para mostrar información sobre energía y condiciones de la batería. También es compatible con el software PowerPanel® Power Management para realizar un apagado correcto de la PC.

Features		Design	
UPS topology *	Line-Interactive	Form factor *	Tower
Output power capacity *	1.5 kVA	Cable length	1.83 m
Output power *	900 W	Product colour *	Black
Input operation voltage (min) *	91 V	Display type	LCD
Input operation voltage (max) *	139 V	Operational conditions	
Input frequency *	60 Hz	Operating temperature (T-T)	0 - 40 °C
Output operation voltage (max)	120 V	Storage temperature (T-T)	-15 - 45 °C
Output frequency	60 Hz	Operating relative humidity (H-H)	0 - 95%
Output voltage regulation	5%	Storage relative humidity (H-H)	0 - 95%
Automatic Voltage Regulation (AVR)	✔	Operating altitude	0 - 15000 m
Maximum current	12 A	Certificates	
Surge energy rating	890 J	Compliance certificates	RoHS
Response time	4 ms	Certification	FCC Clase B, UL
Ports & interfaces		Sustainability	
AC outlet types	NEMA 5-15R	Sustainability certificates	ENERGY STAR
AC outlets quantity	10 AC outlet(s)	Weight & dimensions	
		Width	99 mm
		Depth	249 mm
		Height	348 mm
		Weight	11.3 kg

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 04-APR-2025. Prints or copies of Information are only valid on the printed Publication date