TP-Link Deco X50-Outdoor Doble banda (2,4 GHz / 5 GHz) Wi-Fi 6 (802.11ax) Blanco 1 Interno

Marca : TP-Link

Código del producto: DECO X50-OUTDOOR

Nombre del producto : Deco X50-Outdoor

Sistema Deco X50-Outdoor Wi-Fi 6 Mesh AI AX3000 para exteriores
TP-Link Deco X50-Outdoor. Color del producto: Blanco, Tipo de antena: Interno, Tipo de producto: Sistema de malla. Banda Wi-Fi: Doble banda (2,4 GHz / 5 GHz), Máximo estándar Wi-Fi: Wi-Fi 6 (802.11ax), Estándares de Wi-Fi: Wi-Fi 6 (802.11ax). Asistente virtual: Amazon Alexa & Google Assistant, Compatible con servicios en la nube: TP-Link ID. Voltaje de entrada AC: 100-240 V, Corriente de entrada del adaptador de CA: 0.5 A, Frecuencia de entrada AC: 50/60 Hz. Certificación: CE, FCC, RoHS

Design	
Product type	Mesh system
Product colour *	White
Antenna type *	Internal
Maximum coverage	230 m²

Wireless LAN features	
Wi-Fi band *	Dual-band (2.4 GHz / 5 GHz)
Top Wi-Fi standard *	Wi-Fi 6 (802.11ax)
Wi-Fi standards	Wi-Fi 6 (802.11ax)
WLAN data transfer rate (first band)	2402 Mbit/s
WLAN data transfer rate (second band)	574 Mbit/s
Networking standards	IEEE 802.11a, IEEE 802.11ac, IEEE 802.11ax, IEEE 802.11b, IEEE 802.11g, IEEE 802.11n
Security algorithms	WPA, WPA2, WPA3
Number of guest networks (5 GHz)	1
Number of guest networks (2.4 GHz)	1
Point-to-point protocol over Ethernet (PPPoE)	✔
Dynamic IP	✔
Static IP	✔
IGMP proxy	✔
IGMP snooping	✔
Tagged VLAN	✔
Dynamic DNS (DDNS)	✔
Guest access	✔
Apps supported	TP-Link Deco

Features	
Port forwarding	✔
DHCP client	✔
DHCP server	✔
Universal Plug and Play (UPnP)	✔
Parental control	✔
Works with Amazon Alexa	✔
MU-MIMO technology	✔
MIMO	✔

Ports & interfaces	
Ethernet LAN (RJ-45) ports *	1
Power over Ethernet (PoE)	✔
Ethernet WAN	✔

Power	
AC input voltage	100-240 V
AC adapter input current	0.5 A
AC input frequency	50/60 Hz

Certificates	
Certification	CE, FCC, RoHS

Operational conditions	
Operating temperature (T-T)	-30 - 60 °C
Storage temperature (T-T)	-40 - 70 °C
Operating relative humidity (H-H)	10 - 90%
Storage relative humidity (H-H)	5 - 90%

Weight & dimensions	
Width	110 mm

Features	
Built-in processor	✕
Virtual assistant	Amazon Alexa & Google Assistant
Quality of Service (QoS) support	✔
Cloud services supported	TP-Link ID

Weight & dimensions	
Depth	121.3 mm
Height	215.5 mm

Packaging content	
Number of products included	1 pc(s)
AC adapter included	✔
Ethernet cable	✔

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 15-APR-2025. Prints or copies of Information are only valid on the printed Publication date