

Manhattan 208413 extensor de audio/video Transmisor y receptor AV Negro

Marca : Manhattan

Código del producto: 208413

Nombre del producto : 208413

Manhattan 208413. Tipo: Transmisor y receptor AV, Máxima resolución: 1920 x 1080 Píxeles, Tipos de cable soportados: Cat6. Tecnología de conectividad: Alámbrico, Tipo de conector USB: USB tipo A. Tipo de alimentación: CC, Voltaje de entrada AC: 100 - 240 V, Frecuencia de entrada AC: 50 - 60 Hz. Ancho: 104 mm, Profundidad: 112 mm, Altura: 23 mm. Ancho del paquete: 295 mm, Largo del paquete: 495 mm, Alto del paquete: 322 mm



Features		Power	
Type *	AV transmitter & receiver	Power consumption (transmitter) (max)	3.5 W
Maximum resolution *	1920 x 1080 pixels	Power consumption (receiver) (max)	2 W
Cable types supported	Cat6	External power adapter	✓
Maximum transfer distance	120 m	Operational conditions	
Maximum refresh rate	60 Hz	Operating temperature (T-T)	0 - 50 °C
LED indicators	Activity, Link, Power, USB	Storage temperature (T-T)	-20 - 60 °C
Supported video modes	480p, 720p, 1080i, 1080p	Operating relative humidity (H-H)	5 - 90%
Bandwidth	4.95 Gbit/s	Weight & dimensions	
HDCP	✓	Width	104 mm
Material	Metal	Depth	112 mm
3D	✓	Height	23 mm
Plug and Play	✓	Weight	430 g
HDCP version	1.4	Packaging data	
Product colour	Black	Package width	295 mm
Ports & interfaces		Package depth	495 mm
Connectivity technology *	Wired	Package height	322 mm
RJ-45 input ports	1	Package weight	840 g
RJ-45 output ports	1	Packaging content	
HDMI in	1	AC adapter included	✓
Number of HDMI outputs	1	Manual	✓
HDMI version	1.3	Mounting brackets included	✓
USB ports quantity	3	Technical details	
USB version	2.0	Compliance certificates	UKCA, REACH, Federal Communications Commission (FCC), RoHS, CE
USB connector type	USB Type-A	Logistics data	
DC-in jack	✓	Master (outer) case width	295 mm
Power		Master (outer) case length	495 mm
Power source type	DC	Master (outer) case height	322 mm
AC input voltage	100 - 240 V	Master (outer) case gross weight	10 kg
AC input frequency	50 - 60 Hz	Products per master (outer) case	10 pc(s)
Operating voltage	5 V		
Input current	0.4 A		
Output current	1 A		



0766623208413



766623208413

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.