

## **TP-Link ER7406 enrutador Gigabit Ethernet Negro**

Marca: TP-Link Código del producto: ER7406

Nombre del producto: ER7406

TP-Link ER7406. Estándares de red: IEEE 802.1D, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z, Tipo de interfaz ethernet: Gigabit Ethernet, Ethernet LAN, velocidad de transferencia de datos: 10,100,1000 Mbit/s. Algoritmos de seguridad: 128-bit AES, 192-bit AES, 256-bit AES, DES, MD5, SHA-1, SHA-2, SHA-384, SHA-512. Certificados de cumplimiento: CE, Comisión Federal de Comunicaciones (FCC), RoHS. Cables incluidos: Corriente alterna. Memoria Flash: 128 MB, Memoria interna: 512 MB, Tipo de memoria interna: DDR4





WAN connection		Certificates	
Ethernet WAN * DSL WAN *	×	Compliance certificates	CE, Federal Communications Commission (FCC), RoHS
SIM card slot *	×	Packaging content	
3G/4G USB modem compatibility *	·	Cables included	AC
SFP WAN *	<b>✓</b>	Quick installation guide	✓
Network		Features	
Networking standards *  Ethernet interface type * Ethernet LAN data rates Static route VLAN support  Management features Web-based management * Reset button	IEEE 802.1D, IEEE 802.3, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x, IEEE 802.3z  Gigabit Ethernet 10,100,1000 Mbit/s	Flash memory Internal memory Internal memory type Windows operating systems supported Mac operating systems supported Linux operating systems supported Design Product colour *	128 MB 512 MB DDR4 Windows 10, Windows 2000, Windows 7, Windows 8, Windows 8.1, Windows 98SE, Windows NT, Windows Vista, Windows XP    Black
Ports & interfaces		Rack mounting	✓
Ethernet LAN (RJ-45) ports * Installed SFP modules quantity USB ports quantity  Protocols	5 1 1	Power Power consumption (max) AC input voltage AC input frequency	7.5 W 100 - 240 V 50/60 Hz
			30/00 112
DMZ support DHCP server *	*	Operational conditions  Operating temperature (T-T)  Storage temperature (T-T)  Operating relative humidity (H-H)  Storage relative humidity (H-H)	0 - 50 °C -40 - 70 °C 10 - 90% 5 - 90%

Security		Weight & dimensions	
Security algorithms *	128-bit AES, 192-bit AES, 256-bit AES, DES, MD5, SHA-1, SHA-2, SHA-384, SHA-512	Width Depth Height	294 mm 140 mm 44 mm
URL filtering	✓	rieignit	44 111111
DoS attack prevention	✓		
ARP attack prevention	<b>✓</b>		
ICMP attack prevention	✓		
VPN tunnels quantity	50		





8885020622300

8885020622317

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.