




UNIDAD DE ESTADO SÓLIDO

120Gb, 240Gb, 480Gb, 1Tb, 2Tb



UNIDAD DE ESTADO SÓLIDO

120Gb, 240Gb, 480Gb, 1Tb, 2Tb





UNIDAD DE ESTADO SÓLIDO

120Gb, 240Gb, 480Gb, 1Tb, 2Tb

Soporta funciones S.M.A.R.T., Trim Command, NCQ
Corrección de errores configurable, o Sobreaprovisionamiento configurable por el usuario.
Avanzada tecnología de nivelación de desgaste.

Especificaciones

Interfaz	SATA III	Voltaje	DC 5V
Dimensiones	100 X 69.9 X 7 cm	Temperatura de funcionamiento	0°C~70°C
		4Kb Random Read IOPS	70000
		4KBb Random Write IOPS	5000

Medidas 12 x 10 2.3 cm Peso de producto 300gr Corrugado Depende la piezas



UNIDAD DE ESTADO SÓLIDO

120Gb, 240Gb, 480Gb, 1Tb, 2Tb

120 Gb

Sequential Read:	500MB/s
Sequential Write:	450MB/s
Response Time:	0.2ms

240 Gb

Sequential Read:	500MB/s
Sequential Write:	450MB/s
Response Time:	0.2ms

480 Gb

Sequential Read:	500MB/s
Sequential Write:	450MB/s
Response Time:	0.2ms

1Tb

Sequential Read:	500MB/s
Sequential Write:	450MB/s
Response Time:	0.2ms

2Tb

Sequential Read:	500MB/s
Sequential Write:	450MB/s
Response Time:	0.2ms

Modelo:

	SKU	Ean13
120Gb	STMSSD1B	7503028126699
240Gb	STMSSD2B	7503028126705
480Gb	STMSSD3B	7503028126712
1Tb	STMSSD4B	7503041018292
2Tb	STMSSD5B	7503041018308