



PROYECTORES

PJD7828HDL

Características **principales**

- PortAll: Streaming inalámbrico discreto
- Resolución Full HD 1080p
- 1.3x zoom óptico manual
- Brillo (ANSI lumens): 3.200lm
- SuperColor™: La mejor precisión de color en su clase



Descripción del **producto**

The ViewSonic LightStream™ PJD7828HDL 1080p projector features 3,200 lumens, Full HD 1920 x 1080 native resolution, an intuitive, user-friendly design and a sleek white chassis. Exclusive SuperColor™ technology offers a 6-Segment Color Wheel - 15%+ color brightness, for true-to-life image projection, while SonicExpert™, ViewSonic's proprietary sound enhancement technology, powers a 10W cube speaker to deliver incredibly clear and audible sound. PortAll™ - a neatly designed enclosed HDMI/MHL connection compartment, supports wireless HDMI dongles or MHL connectors, while a cable management hood eliminates unsightly cable clutter. With shorter throw ratio, 1.3x optical zoom, smart design, and extensive connectivity, the PJD7828HDL provides flexible and quick set-up. The PJD7828HDL is the ideal projector for both high definition presentations and vibrant multimedia entertainment.

Visítanos ■ www.viewsonic.com

PRODUCT SPECIFICATION

Resolution:	1920x1080
Brightness (ANSI Lumens):	3,200lm
Contrast (Max.):	22,000 :1
Lamp Hour (Normal / SuperEco):	4000hrs / 10000hrs
Throw Ratio in Meters (Wide ~ Tele):	1.15~1.5
Optical Zoom:	1.3x
Digital Zoom:	0.8x~2.0x
Screen Size:	30"~300"
Projection Offset:	110%%±5%
Display Colours:	1.07 Billion Colors
Keystone:	+/- 40° (Vertical)
Noise min (Normal / Eco):	35dBdB / 30dBdB
Speaker:	10W Cube

INPUT CONNECTIVITY

HDMI/MHL:	1
HDMI In:	1
VGA-in:	1
Component Input:	shared with VGA-in
S-Video:	1
Composite Input:	1
Audio-in (3.5mm):	1
USB Type A:	1 (5V/2A)
USB Type B:	N/A
Mini USB:	1
Micro USB cable:	1 (5V/2A)
Microphone in (3.5mm):	share with audio in 2
SD Card reader:	N/A

OUTPUT CONNECTIVITY

VGA-out:	1
Audio-out (3.5mm):	1

CONTROL

RS232 (9 pin):	1
Network Mangment (LAN cable):	N/A
12V Power Trigger:	N/A

DIMENSIONS AND POWER

Dimension (WxDxH):	316 mm(W) x 228 mm(D) x 103.7 mm(H) 12.44" (W) x 8.98 " (D) x 4.08" (H)
Net Weight:	2.4 kg (5.29 lb)
Power Source:	100~240Vac 50/60Hz
Power Consumption:	330W (Max.)

SUPPLIED ACCESSORIES

Power cord:	1
VGA cable:	1
Remote Control (with batteries):	1
Cable cover:	1
Quick Start Guide & CD:	1

LANGUAGES

On Screen Display:	21 OSD languages support. (English, France, Spanish, Thai, Korea, Germany, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic)
--------------------	--

REGULATIONS

Standard:	CB,CCC, cTUVus, CE, FCC,C-Tick, ROHS, REACH, SVHC, WEEE, ErP, EAC,TUV-S Mark(Argentina), PSB, KCC, KC, SASO, CECP, NOM, Mexico Energy Test
-----------	--

WARRANTY

**Warranty offered may differ from market to market